Environmental Status Report For Kudag Bauxite Mine at

Post & Teh.: Samri, (Kusmi)

Dist: Balrampur-Ramanujganj(C.G.)

Duration: October-November-December-2019

Name of Industry



M/s. Hindalco Industries Limited.,

Name of Laboratory:-



QCI-NABET Accredited EIA Consultant
MoEF&CC (GOI) and NABL Recognized Laboratory
ISO 9001:2015, ISO 14001:2015, OHSAS 18001:2007

60, Bajiprabhu Nagar, Nagpur - 440 033, MS Lab. & Consultancy: FP-34, 35, Food Park, MIDC, Butibori, Nagpur - 441122 Ph.: (0712) 2242077, 9373287475

Email: info@anacon.in, ngp@anacon.in website: www.anaconlaboratories.com

Rapombetta

Agent of Mines Samn Mines Division Hindalco Industries Ltd

Foreword

The protection of environment plays a crucial role in maintaining the local environment quality for any mining industry. Hence compliance of the statutory requirements becomes very important to conserve the ecological balance within and surrounding the mine area. Therefore, environment protection is becoming a prerequisite for sustainable development. In line with this requirement, the management of M/s Hindalco Industries Ltd. has adopted a corporate responsibility of environment protection.

In order to comply with the Environment protection act, to fulfill statutory requirement and to be in tune with Environmental Preservation and sustainable development, M/s Hindalco Industries Ltd. has retained ANACON LABORATORIES PVT. LTD., Nagpur as Environment Consultants and for various Environmental issues related to their mines.

This report presents the Environmental Status for the period October-2019 to December-2019 as compliance to the statutory requirements.

The co-operation extended by the Staff and Management of M/s Hindalco Industries Ltd. during the work execution period is gratefully acknowledged.

For ANACON LABORATO

Place : Nagpur

Date : December, 2019



Introduction

1.1 Introduction

Hindalco Industries Limited (Hindalco) is one among the flagship companies of the Aditya Birla Group of Industries and is one of the largest corporate groups in India. This group is a leading manufacturer of Aluminum in India, having integrated facilities encompassing bauxite, mining, refining and smelting to achieve Aluminum.

Various processing units of Hindalco are strategically located in different parts of the nation to achieve optimum benifits. Over the past few decades the group has grown multifold in its production capacities, product mix and diversification in mining. The Chhattisgarh Environment Conservation Board (CECB) granted permission for establishing the Bauxite Mine to Hindalco at block Tatijharia, Kudag and Samri mines in Balrampur District of Chhattisgarh State.

HINDALCO INDUSTRIES LTD., awarded the work to M/s ANACON LABORATORIES PVT. LTD. Nagpur(ALPL) for carrying out Environmental monitoring of parameters for assessing pollution levels and preparation of monthly reports (October-November-December-2019) as per the requirement of Chhattisgarh Environment Conservation Board (CECB) and Ministry of Environment, Forest and Climate Change (MoEF&CC) for Kudag mining lease in Balrampur District, Chhattisgarh State.

1.2 Background Information of Kudag Mine

Hindalco was granted Kudag Bauxite mining lease over an area of 377.116 hec. in Kudag village, Post office-Dumarkholi, Tehsil-Samri (Kusmi) of Balrampur district, Chhattisgarh on 24/12/1996 for a period of 20 years. As per the Mines and Mineral (Development and Regulation) Amendment Act, 2015, Kudag lease has been extended up to another 30 years i.e 23/12/2046. The mining operations were started on 02/07/1997. The production capacity of Bauxite is 0.6 Lakh Tonnes Per Annum (LTPA).

1.3 Salient Features of Kudag Bauxite Mine

The deposits occur in Kudag block, Post office Dumarkholi, Tehsil-Samri (Kusmi) of Balrampur district. This deposit has been identified as one of the resources to cater the raw material requirements of the Hindalco Alumina refinery at Renukoot, Uttar Pradesh. The salient features of the project are presented below in Table 1.



Details of Salient Features

Table: 1

Salient Features of Kudaq Bauxite Mines

SI. No.	Particulars	Details
1.	Survey of India Toposheet No.	64 M /15
2.	Latitude	23° 26′ 02″N to 23° 29′ 00″N
3.	Longitude	83° 51′ 00″E to 83° 59′ 00″E
4.	Elevation	1145-m above Mean Sea Level
5.	Climatic Conditions (as per IMD, Ambikapur)	Annual maximum temperature: 30.3°C Annual minimum temperature: 17.7°C Average annual rainfall: 1401.1 mm
6.	Mining lease area	377.116 Hec.
7.	Method of mining	Open cast (Semi-Mechanized)
8.	Mode of transportation	Trucks
9.	Land use	Agricultural and Barren land
10.	Nearest Road	Samri to Kusmi (17 km)
11.	Nearest Airport	Ranchi Airport (151,09 Km)
12.	Nearest Town	Ambikapur (127 km, SW)

1.4 Environmental Monitoring

Regular monitoring of environmental parameters is of immense importance to assess the status of environment during mining operation. With the knowledge of baseline conditions, the monitoring program will serve as an indicator for any deterioration in environmental conditions due to mining operation of the project. Suitable mitigation steps will be taken in time to safeguard the environment based on monitoring reports. Monitoring is important in the control of pollution since the efficiency of control measures can only be determined by monitoring.

In order to find out the impact of mining activity on sensitive receptors, it is necessary to monitor Environmental Quality to know the level of concentrations of pollutants within and around the mining lease area. Accordingly Hindalco Industries through ALPL has been monitoring air, water and noise quality on monthly basis during these months (Table-2).



Details of Salient Features

1.5 Air Environment

1.5.1 Ambient Air Quality Monitoring:

Ambient Air Quality and Fugitive emission monitored at 8 following locations with reference to Kudag mine lease area shown in (Fig.-1).

Table 2

Locations of Ambient Air Quality Monitoring (AAQM) (377.116 hec.)

Sr. No.	Core Zone	Sr. No.	Buffer Zone
1	Sairaidh Campus	5	Kutku Village
2	New Kudag/Nr.Weigh Bridge	6	Rajendrapur
3	Old Kudag/Mining Area	7	Tatijharia Village
4	Samri Gopatu/Nr. Weigh Bridge	8	Virhorepat

The sampling stations are selected at the above mentioned locations, in downwind and upwind directions of the mining site. ALPL is carrying out regular monitoring for PM_{10} , $PM_{2.5}$, SO_2 , NO_X and Pb, Hg, As and Cr at above Ambient Air Quality Monitoring (AAQM) locations. The dust fall rate was measured in the mining area and Khas kudag during October-November-December-2019. The AAQM sampling sites are selected considering seasonal variation in wind speed and wind direction.

Sampling Duration and Frequency

Ambient air quality monitoring was carried out for the parameters PM_{10} , $PM_{2.5}$, SO_2 , NO_X and Pb, Hg, As and Cr from October-November-December-2019 as per CPCB norms.

Data is compared with the standards mentioned in the Gazette Notification of the Central Pollution Control Board (CPCB) (Nov-18, 2009) and as per consent conditions mentioned in consent letter.



Details of Salient Features

1.6 Meteorology: Wind Pattern

Meteorology: Wind Pattern

The data of wind pattern collected during the study period (October-November-December-2019) indicates that the wind was blowing predominately from (S and SW) directions, during study period.

Wind Frequency Distribution Data

Sr. No.	Directions / Wind Classes (m/s)	0.5 - 2.1	2.1 - 3.6	3.6 - 5.7	5.7 - 8.8	8.8 - 11.1	>= 11.1	Total (%)
1	348.75 - 11.25	0.004082	0.008163	0.000000	0.000000	0.000000	0.000000	0.012245
2	11.25 - 33.75	0.019048	0.008163	0.001361	0.000000	0.000000	0.000000	0.028571
3	33.75 - 56.25	0.034014	0.012245	0.000000	0.000000	0.000000	0.000000	0.046259
4	56.25 - 78.75	0.029932	0.019048	0.000000	0.000000	0.000000	0.000000	0.048980
5	78.75 - 101.25	0.019048	0.004082	0.000000	0.000000	0.000000	0.000000	0.023129
6	101.25 - 123.75	0.061224	0.006803	0.000000	0.000000	0.000000	0.000000	0.068027
7	123.75 - 146.25	0.051701	0.002721	0.000000	0.000000	0.000000	0.000000	0.054422
8	146.25 - 168.75	0.068027	0.001361	0.000000	0.000000	0.000000	0.000000	0.069388
9	168.75 - 191.25	0.118367	0.002721	0.000000	0.000000	0.000000	0.000000	0.121088
10	191.25 - 213.75	0.115646	0.001361	0.000000	0.000000	0.000000	0.000000	0.117007
11	213.75 - 236.25	0.089796	0.005442	0.000000	0.000000	0.000000	0.000000	0.095238
12	236.25 - 258.75	0.058503	0.014966	0.000000	0.000000	0.000000	0.000000	0.073469
13	258.75 - 281.25	0.055782	0.012245	0.001361	0.000000	0.000000	0.000000	0.069388
14	281.25 - 303.75	0.039456	0.014966	0.004082	0.000000	0.000000	0.000000	0.058503
15	303.75 - 326.25	0.019048	0.035374	0.001361	0.000000	0.000000	0.000000	0.055782
16	326.25 - 348.75	0.031293	0.009524	0.000000	0.000000	0.000000	0.000000	0.040816
	Sub-Total	0.814966	0.159184	0.008163	0.000000	0.000000	0.000000	0.980978
	Calms							
	Missing/Incomplete							
	Total				A Ver			1.000000

Summary of Wind Pattern

Season	First Predominant Wind Direction	Second Predominant Wind Direction	Calm Condition
October-November- December-2019	S (12.1%)	SW (11.7%)	1.7%






Figure.01: Wind Rose Diagram (Oct-Nov-Dec-2019)




Figure.02: Wind Class Frequency Distribution (Oct-Nov-Dec-2019).



Details of Salient Features

1.7 MONITORED PARAMETERS AND FREQUENCY OF SAMPLING

Methods and Instruments used for Sampling

The air samples were analyzed as per methods specified by Central Pollution Control Board (CPCB).

The levels of Particulate Matter (PM_{10}), Particulate Matter ($PM_{2.5}$), Sulphur Dioxide (SO_2), Oxides of Nitrogen (NO_X), Pb, Hg, As and Cr were monitored for establishing the baseline status. PM_{10} was collected with the help of Respirable Particulate Sampler operating 24 hours by drawing air which passes through the cyclone at the rate of 1.0 -1.3 m 3 /min which collects the particles less than 10 μ m diameter over glass fiber filter paper. The dust deposited over the filter paper is measured as PM_{10} and the smaller particulates from 2.5 μ m are collected into the Membrane Filter Paper. The dust fall rate was measured using dust fall jar. The jar was exposed for one month in the mining area and Samri Chowk during pre and post monsoon period. The jar was filled with 2 lit of distilled water. The water in the jar is mixed with copper sulphate solution (0.02 N solutions) to prevent any growth of algae. The water level in the jar is constantly maintained in such a way that 2 lit of water is always retained. The measurement techniques used for various pollutants and other details are given in (Table 3).

Earmarked samples were collected for Particulate Matter-PM₁₀, Particulate Matter-PM_{2.5}, SO₂ and NOx for 24 hourly. Collected samples were sent to Laboratories for analysis.

Table 3.0

Measurement Techniques for various pollutants

SI. No.	Parameter	Technique	Technical Protocol	Minimum Reportable Value (µg/m³	
1.	Respirable Particulate Matter	Respirable Dust Sampler (Gravimetric Method)	IS-5182 (Part-23)	5	
2.	Particulate Matter 2.5	Respirable Dust Sampler (Gravimetric Method)	Gravimetric Method	5	
3.	Sulphur Dioxide	Modified West and Gaeke	IS-5182 (Part - II)	4	
4.	Oxide of Nitrogen	Jacob & Hochheiser Method	IS-5182 (Part - VI)	4	
5.	Pb, As, Hg, Cr	Acid Digestion Method	EPA Method	0.1	
6.	Dust Full	Gravimetric	IS-5182 (Part-I)	-	



Details of Salient Features

Table 4

Statistical Analysis

Location	Month & Year	PM-10 (μg/m ³)	PM-2.5 (μg/m ³)	SO ₂ (μg /m ³)	NO _x (μg/m ³)	Pb (μg/m ³)	Hg (μg /m ³)	As (ng/m ³)	Cr
Core Zone				1 10	T.VLO.	I (PE/III)	(µg/m ⁻)	1 (ng/m-)	(μg/m ³)
	Oct-2019	54.6	21.7	7.6	18.3	0.017	ND	ND	ND
Sairaidh Campus	Nov-2019	61.7	23.2	9.4	20.6	0.020	ND	ND	ND
	Dec-2019	67.7	24.7	8.2	18.5	0.018	ND	ND	ND
New Kudag/Nr.	Oct-2019	61.8	26.3	8.5	22.1	0.016	ND	ND	ND
Weigh Bridge	Nov-2019	64.9	25.2	8.7	19.6	0.021	ND	ND	ND
	Dec-2019	60.8	22.8	7.4	17.9	0.017	ND	ND	ND
Old	Oct-2019	57.3	22.5	7.2	18.7	0.010	ND	ND	ND
Kudag/Mining	Nov-2019	56.1	20.1	8.5	18.5	0.016	ND	ND	ND
Area	Dec-2019	61.6	27.2	8.5	19.3	0.014	ND	ND	ND
Samri Gopatu/	Oct-2019	60.4	24.1	8.4	21.6	0.015	ND	ND	ND
Nr. Weigh	Nov-2019	59.8	23.9	7.6	17.9	0.018	ND	ND	ND
Bridge	Dec-2019	63.2	24.8	9.3	18.5	0.012	ND	ND	ND
CPCB Stan	dards	100 (24 hrs)	60 (24 hrs)	80 (24 hrs)	80 (24 hrs)	1.0 (24 hrs)	-	6.0 (annual)	
Minimum		54.6	20.1	7.2	17.9	0.010	-		-
Maximu	ım	67.7	27.2	9.4	22.1	0.021			
Averag	ge	60.8	23.9	8,3	19.3	0.016			
98% 1	9	67.1	27.0	9.4	22.0	0.021	***		

- The Average Concentration of PM₁₀ within the Core Zone of Kudag Lease is 60.8 μg/m³.
- The Average Concentration of PM_{2.5} within the Core Zone of Kudag Lease is 23.9 μg/m³.
- The Average Concentration of SO₂ within the Core Zone of Kudag Lease is 8.3 μg/m³.
- The Average Concentration of NOx within the Core Zone of Kudag Lease is 19.3 μg/m³.
- The Average Concentration of Pb within the Core Zone of Kudag Lease is 0.016 μg/m³.

Conclusion :-

The Average Concentration within the Core Zone of Kudag Lease during this period (October-November-December-2019), it is within permissible limits as per CPCB Standards.



Details of Salient Features

Location	Month & Year	PM-10 (µg/m ³)	PM-2.5 (μg/m ³)	SO ₂ (μg /m ³)	NO _x (μg /m ³)	Pb (μg/m ³)	Hg (µg/m³)	As (ng/m ³)	Cr (μg/m ³)
Buffer Zone					1 40 4	1 (58/11)	(88/111/	(105/111-)	(hg/m-)
	Oct-2019	59.8	23.9	7.6	17.9	0.019	ND	ND	ND
Kutku Village	Nov-2019	57.0	22.5	7.1	17.9	0.017	ND	ND	ND
	Dec-2019	62.4	22.7	8.6	19.3	0.015	ND	ND	ND
	Oct-2019	56.1	20.1	8.5	18.5	0.021	ND	ND	ND
Rajendrapur	Nov-2019	60.6	21.6	8.4	23.7	0.024	ND	ND	ND
	Dec-2019	59.4	21.2	7.9	17.6	0.017	ND	ND	ND
W	Oct-2019	61.2	22.7	7.9	19.3	0.026	ND	ND	ND
Tatijharia Village	Nov-2019	65.5	33.4	12.2	25.4	0.025	ND	ND	ND
0	Dec-2019	64.2	24.7	9.3	21.6	0.020	ND	ND	ND
	Oct-2019	62.4	18.1	6.9	20.6	0.019	ND	ND	ND
Virhorepat	Nov-2019	56.0	20.5	8.3	18,2	0.023	ND	ND	ND
	Dec-2019	57.9	20.8	8.5	19.5	0.019	ND	ND	ND
CPCB Sta	ndards	100 (24 hrs)	60 (24 hrs)	80 (24 hrs)	80 (24 hrs)	1.0 (24 hrs)	-	6.0 (annual)	-
Minimum		56.0	18.1	6.9	17.6	0.015			
Maxim	um	65.5	33.4	12.2	25.4	0.026		-	
Avera	ge	60.2	22.7	8.4	20.0	0.020		102.0	***
98%	le	65.2	31.5	11.6	25.0	0.026			

- The Average Concentration of PM10 within the Buffer Zone of KudagLease is 60.2 μg/m³.
- The Average Concentration of PM25 within the Buffer Zone of KudagLease is 22.7 μg/m³.
- The Average Concentration of SO₂ within the Buffer Zone of KudagLease is 8.4 μg/m³.
- The Average Concentration of NOx within the Buffer Zone of KudagLease is 20.0 µg/m³.
- The Average Concentration of Pb within the Buffer Zone of KudagLease is 0.020 μg/m³.

Conclusion:-

The Average Concentration within the Buffer Zone of Kudag Lease during this period (October-November-December-2019). It is within permissible limits as per CPCB Standards.



Details of Salient Features

Month-wise Summary of Statistical Analysis

Kudag Lease (Core Zone):-

3.1 Ambient Air Quality:

Ambient air quality has been generated as per NAAQS 2009 for the month of October-2019 to December-2019. PM_{10} , $PM_{2.5}$, SO_2 & NO_X , The values obtained were then compared vis-a-vis the standards prescribed by CPCB for Industrial/Rural / Residential uses.

3.2 Presentation of Results:

The summary of Ambient Air Quality monitoring results from October-2019 to December-2019 are presented in detail in Table 4.0. 98th percentile; maximum and minimum values etc. have been computed from the collected raw data for all the AAQ monitoring station. The data has been compared with the standards prescribed by Central Pollution Control Board (CPCB)/NAAQS for residential and rural zone.

A. Particulate Matter-PM₁₀:

The Minimum and maximum concentrations for Particulate Matter- PM_{10} were recorded as $54.6 \mu g/m^3$ and $67.7 \mu g/m^3$ respectively. The minimum concentration was recorded at Sairaidh Campus. The maximum concentration was also recorded at Sairaidh Campus. The average concentration of PM10 was $60.8 \mu g/m^3$.

B. Particulate Matter-PM_{2.5}:

The Minimum and maximum concentrations for Particulate Matter- $PM_{2.5}$ were recorded as $20.1 \mu g/m^3$ & $27.2 \mu g/m^3$ respectively. The minimum concentration was recorded at Old Kudag/Mining Area. The maximum concentration was also recorded at Old Kudag/Mining Area. The average concentration of $PM_{2.5}$ was $23.9 \mu g/m^3$.

C. Sulphur Dioxide (SO₂):

The minimum and maximum for SO_2 concentrations were recorded as $7.2\mu g/m^3$ and $9.4\mu g/m^3$ at respectively. The minimum concentration was recorded at Old Kudag. The maximum concentration was also recorded at Sairaidh Campus. The average concentration of SO_2 was $8.3\mu g/m^3$.

D. Nitrogen Oxide (NO_x):



Details of Salient Features

The minimum and maximum for NO_X concentrations were recorded as $17.9\mu g/m^3$ and $22.1\mu g/m^3$. The minimum concentration was recorded at Samri-Gopatu and the maximum concentration was recorded at New Kudag/Nr Weigh Bridge. The average concentration of NO_X was $19.3\mu g/m^3$.

E. Lead (Pb):

Maximum Lead detected in PM_{10} samples was $0.021\mu g/m^3$ at New Kudag/Nr. Weigh Bridge location and the minimum lead in PM_{10} sample was $0.010\mu g/m^3$ detected at Old Kudag location.

No lead could be detected in PM_{2.5} samples at any of the Ambient Air samples at any of the locations.

F. Mercury (Hg):

Mercury was not detected at any of the locations in PM_{10} samples as well as $PM_{2.5}$ Samples.


G. Arsenic (As):


Arsenic was not detected at any of the locations in PM_{10} samples as well as $PM_{2.5}$ Samples.


H. Chromium (Cr):

Chromium was not detected at any of the locations in PM_{10} samples as well as $PM_{2.5}$ Samples.






















Details of Salient Features

Kudag Lease (Buffer Zone):-

3.3 Ambient Air Quality:

Ambient air quality has been generated as per NAAQS 2009 for the month of October-2019 to December-2019. PM_{10} , $PM_{2.5}$, SO_2 & NO_X , The values obtained were then compared vis-a-vis the standards prescribed by CPCB for Industrial/Rural / Residential uses.

3.3.1 Presentation of Results:

The summary of Ambient Air Quality monitoring results from October-2019 to December-2019 are presented in detail in Table 4.0. 98th percentile; maximum and minimum values etc. have been computed from the collected raw data for all the AAQ monitoring station. The data has been compared with the standards prescribed by Central Pollution Control Board (CPCB)/NAAQS for residential and rural zone.

A. Particulate Matter-PM₁₀:

The Minimum and maximum concentrations for Particulate Matter-PM₁₀ were recorded as 56.0µg/m³ and 65.5µg/m³ respectively. The minimum concentration was recorded at Virhorepat. The maximum concentration was also recorded at Tatijhara village. The average concentration of PM10 was 60.2µg/m³.

B. Particulate Matter-PM_{2.5};

The Minimum and maximum concentrations for Particulate Matter- $PM_{2.5}$ were recorded as $18.1 \mu g/m^3$ & $33.4 \mu g/m^3$ respectively. The minimum concentration was recorded at Virhorepat. The maximum concentration was also recorded at Tatijhara village. The average concentration of $PM_{2.5}$ was $22.7 \mu g/m^3$.

C. Sulphur Dioxide (SO₂):

The minimum and maximum for SO_2 concentrations were recorded as $6.9\mu g/m^3$ and $12.2\mu g/m^3$ at respectively. The minimum concentration was recorded at Virhorepat. The maximum concentration was also recorded at Tatijhara village. The average concentration of SO_2 was $8.4\mu g/m^3$.



Details of Salient Features

D. Nitrogen Oxide (NO_x):

The minimum and maximum for NO_x concentrations were recorded as $17.6\mu g/m^3$ and $25.4\mu g/m^3$. The minimum concentration was recorded at Rajendrapur location and the maximum concentration was recorded at Tatijhara village. The average concentration of NO_x was $20.0\mu g/m^3$.

E. Lead (Pb):

Maximum Lead detected in PM_{10} samples was $0.026\mu g/m^3$ at Tatijhara village location and the minimum lead in PM_{10} sample was $0.015\mu g/m^3$ detected at Kutku village location.

No lead could be detected in $PM_{2.5}$ samples at any of the Ambient Air samples at any of the locations.

F. Mercury (Hg):

Mercury was not detected at any of the locations in PM_{10} samples as well as $PM_{2.5}$ Samples.


G. Arsenic (As):


Arsenic was not detected at any of the locations in PM_{10} samples as well as $PM_{2.5}$ Samples.


H. Chromium (Cr):

Chromium was not detected at any of the locations in PM_{10} samples as well as $PM_{2.5}$ Samples.






















Details of Salient Features

1.8 Noise Environment

The Director General of Mines Safety in its circular No. DG (Tech)/18 of 1975, has prescribed the noise level in mining occupations (TLV) for workers, in an 8 hour shift period with unprotected ear as 90 dB(A) or less. There will be some noise sources in mines, which produce noise levels above 90 dB(A), however; the workers are not expected to be exposed continuously for 8 hours. In order to maintain this statutory requirement noise monitoring has been carried out in and around the mining lease area.

Work zone noise level in the mining area shall increase due to blasting excavation and transportation. The impacts due to the mining activities on the noise levels shall be negligible, if all the precautions for the elimination of the noise are taken. The mining activities will be undertaken during daytime only. The daytime equivalent noise levels, when all the machineries are in operation, shall be minimized as the machineries have been provided with control equipment. Noise monitoring carried out on monthly basis at mining site; Core Zone and Buffer Zone areas shown in Fig. 3.

Identification of sampling locations

Noise at different noise generating sources has been identified based on the activities in the village area and ambient noise due to traffic.

The noise monitoring has been conducted for determination of ambient noise levels in the mining area and villages. The noise levels at each location were recorded for 24 hours.

Instrument used for monitoring

Noise levels were measured using integrated sound level meter Model no. HTC-SL-1352. This instrument is capable of measuring the Sound Pressure Level (SPL), Leq.

Method of Monitoring

Sound Pressure Level (SPL) measurements were monitored at eight locations. The readings were taken for every hour for 24 hours. The day noise levels have been monitored during 6 am to 10 pm and night levels during 10 pm to 6 am at eight locations within 10-km radius of the study area.

Noise level monitoring was carried out continuously for 24 hours with one hour interval starting at 06.00 hrs to 06.00 hrs next day.



Details of Salient Features

Noise levels monitored during day and night at Four locations are found to be below in the Mining Area than the stipulated standard of CPCB for Industrial area as 75dB(A) and 70dB(A) for day and night respectively as given in **(Table 5)**.

Table 5

Noise Emission Monitoring Report

SR. NO.	LOCATION	Manth	Noise	-dB(A)
SK. NO.	LOCATION	Month	Day Time	Night Time
Core Zone				
S. 100	No. 10 Telephone Control	October-2019	61.4	53.7
1.	New Kudag/Nr. Weigh Bridge	November-2019	62.5	54.2
	onage .	December-2019	63.2	47.5
7018-11		October-2019	58.6	46.2
2.	Old Kudag/Mining Area	November-2019	60.2	48.1
		December-2019	56.8	45.3
Buffer Zoi	ne			
		October-2019	56.8	45.6
1.	Rajendrapur	November-2019	53.7	42.4
		December-2019	54.9	43.8
		October-2019	63.7	50.8
2.	Tatijharia Village	November-2019	62.7	52.5
		December-2019	59.4	47.2
CPCB Star	ndards			E CHELLES
Industrial	Area		75	70
Residentia	al area	Male Has winned in	55	45

<u>Conclusion:</u> The Noise Monitoring Results at Kudag Lease during this period (October-November-December-2019), it is within permissible limits as per CPCB Standards.

Table 6
HEMM Spot Noise Level Monitoring

Unit: dB(A) Lea

SI.		October-2019		Novem	ber-2019	December-2019	
No.	Location	Min.	Max.	Min.	Max.	Min.	Max.
1.	Nr. Weigh Bridge	61.8	72.5	62.2	72.9	61.9	70.8
2.	Mining Area	65.6	75.4	64.9	76.2	63.5	75.2



Details of Salient Features

Table 7

Dust fall Rate

SI. No.	Location Old Kudag/Mining Area	December-2019
		Rate (MT/km²/Month)
1.	Old Kudag/Mining Area	16.32

2.0 Water Quality Monitoring

The existing status of water quality for ground water was assessed by collecting the water samples from underground wells from the mining area/old kudag.

The purpose of the study is to assess the water quality characteristics for critical parameters, evaluate the impacts on agricultural productivity, habitat conditions, recreational resources and aesthetics in the vicinity and identification of impact on water quality by this project and related activities.

The physico-chemical analysis of water samples collected during the study period is given in **(Table-8 and Fig.5)**. The overall water quality found to be below the stipulated standards of IS 10500-2012 for ground water & found to be fit for drinking purpose for tested parameters. Thus the impacts due to mining activities have been found to be insignificant.

The drinking water is supplied by the tankers from for-away sources. Hence, additional care now be taken to chlorinate the tankers before leaving the supply source.



Details of Salient Features

Table 8

Report on Chemical Examination of Ground Water Quality (December-2019)

Location: GW1) Saraidih (Hindalco Campus)
Sample Source:-Borewell Water

TEST RESULTS

Sr. No.	Test Parameter	Measurement Unit	Test Method	NAME OF THE OWNER OWNER OF THE OWNER	10500 : 2012 er - Specification)	Total Daniel
	Took Fording to	modernent ont	rest method	Acceptable Limit	*Permissible Limit	Test Result
1,	pH value		IS 3025 (Part 11)	6.5 to 8.5	No relaxation	7.16 at 25°C
2.	Turbidity	NTU	IS 3025 (Part 10)	1	5	0.6
3.	Colour	Hazen units	IS 3025 (Part 4)	5	15	1
4.	Odour		IS 3025 (Part 5)	Agreeable	Agreeable	Agreeable
5.	Taste		IS 3025 (Part 8)	Agreeable	Agreeable	Agreeable
6.	Iron (as Fe)	mg/l	IS 3025 (Part 2)	1.0	No relaxation	0.13
7.	Free residual chlorine	mg/l	IS 3025 (Part 26)	Min. 0.2	1	< 0.1
8.	Total dissolved solids	mg/l	IS 3025 (Part 16)	500	2000	452
9.	Fluoride (as F)	mg/l	IS 3025 (Part 60)	1.0	1.5	0.69
10.	Cyanide (as CN)	mg/l	IS 3025 (Part 27)	0.05	No relaxation	< 0.005
11.	Chloride (as CI)	mg/l	IS 3025 (Part 32)	250	1000	54.73
12.	Total Alkalinity (as CaCO ₃)	mg/l	IS 3025 (Part 23)	200	600	121.69
13.	Total hardness (as CaCO ₃)	mg/l	IS 3025 (Part 21)	200	600	187.74
14.	Calcium (as Ca)	mg/l	IS 3025 (Part 40)	75	200	51.64
15.	Magnesium (as Mg)	mg/l	IS 3025 (Part 46)	30	100	14.28
16.	Sulphate (as SO ₄)	mg/l	IS 3025 (Part 24)	200	400	18,52
17.	Nitrate (as NO ₃)	mg/l	APHA Method	45	No relaxation	9.76
18.	Copper (as Cu)	mg/l	IS 3025 (Part 2)	0.05	1.5	< 0.03
19.	Manganese (as Mn)	mg/l	IS 3025 (Part 2)	0.1	0.3	< 0.05
20.	Mercury (as Hg)	mg/l	IS: 3025 (Part 48)	0.001	No relaxation	< 0.0005
21.	Cadmium (as Cd)	mg/l	IS: 3025 (Part 41)	0.003	No relaxation	< 0.001
22.	Selenium (as Se)	mg/l	IS: 3025 (Part 56)	0.01	No relaxation	< 0.001
23.	Arsenic (as As)	mg/l	IS: 3025 (Part 37)	0.01	No relaxation	< 0.01
24.	Aluminium (as Al)	mg/l	IS: 15302	0.03	0.2	< 0.005
25.	Lead (as Pb)	mg/l	IS: 3025 (Part 47)	0.01	No relaxation	< 0.001
26.	Zinc (as Zn)	mg/l	IS 3025 (Part 2)	5	15	1.2



Sr.	Test Parameter	Measurement	Test Method	As per IS (Drinking Wate	Test Result					
		Unit	Tool meaned	Acceptable Limit	*Permissible Limit	Test Result				
27.	Nickel (as Ni)	mg/l	IS 3025 (Part 2)	0.02	No relaxation	< 0.01				
28.	Total Chromium (as Cr)	mg/l	IS 3025 (Part 2)	0.05	No relaxation	< 0.03				
29.	Barlum (as Ba)	mg/l	Annexure F of IS 13428	0.7	No relaxation	< 0.01				
30.	Ammonia (as N)	mg/l	IS 3025 (Part 34)	0.5	No relaxation	< 0.1				
31.	Sulphide (as H ₂ S)	mg/l	IS 3025 (Part 29)	0.05	No relaxation	< 0.03				
32.	Chloramines (as Cl ₂)	mg/l	IS 3025 (Part 26)	4.0	No relaxation	< 0.05				
33.	Molybdenum (as Mo)	mg/l	IS 3025 (Part 2)	0.07	No relaxation	< 0.001				
34.	Silver (as Ag)	mg/l	Annexure J of IS 13428	0,1	No relaxation	< 0.001				
35.	Polychlorinated Biphenyls (PCB)	µg/l	USEPA 508	0.5	No relaxation	< 0.03				
36.	Boron (as B)	mg/l	IS 3025 (Part 2)	0.5	2.4	< 0.1				
37.	Mineral Oil	mg/l	IS 3025 (Part 39)	0.5	No relaxation	< 0.001				
38.	Tri Halo Methane									
	a. Bromoform			0.1	No relaxation	Absent				
	b. Dibromochloromethane			0.1	No relaxation	Absent				
	c. Bromodichloromethane	mg/l	APHA 6232	0.06	No relaxation	Absent				
	d.Chloroform	Mary Sales		0.2	No relaxation	Absent				
39.	Phenolic compounds (as C ₆ H ₅ OH)	mg/l	IS 3025 (Part 43) :1001	0.001	0.002	< 0.001				
40.	Anionic detergents (as MBAS)	mg/l	IS 13428:2005 (Annex K)	0.2	1.0	< 0.01				
41.	Polynuclear aromatic hydrocarbon (PAH)	µg/I	USEPA: 550	0.1	No relaxation	< 0.03				
42.	Total coliform	Per 100 ml	IS 15185	Absent	Absent	Absent				
43.	Escherichia coli	Per 100 ml	IS 15185 : 2016	Absent	Absent	Absent				



Details of Salient Features

Sr. No.	Test Parameter	Measurement Unit	Test Method	As per IS 10500 : 2012 (Drinking Water - Specification)	Test Result			
44.	Pesticides residues							
i.	Alpha-HCH	µg/l	USEPA 508	0.01	< 0.01			
ii.	Beta HCH	μg/l	USEPA 508	0.04	< 0.03			
iii,	Delta- HCH	µg/l	USEPA 508	0.04	< 0.03			
iv.	Alachlor	μg/l	USEPA 508	20	< 0.03			
٧.	Aldrin /Dieldrin	µg/I	USEPA 508	0.03	< 0.03			
vi.	Atrazine	μg/l	USEPA 1657	2	< 0.03			
vii.	Butachlor	µg/l	USEPA 508	125	< 0.03			
viii.	Chlorpyrifos	µg/I	USEPA 1657	30	< 0.03			
ix.	DDT and its Isomers	μg/l	USEPA 508	1	< 0.03			
X.	Gamma - HCH (Lindane)	µg/l	USEPA 508	2	< 0.03			
xi.	2,4-Dichlorophenoxyacetic acid	µg/l	USEPA 1657	30	< 0.03			
xii.	Endosulphan	µg/l	USEPA 508	0.4	< 0.03			
xiii.	Ethion	µg/l	USEPA 1657	3	< 0.03			
xiv.	Isoproturon	μg/l	USEPA 1657	9	< 0.03			
XV.	Malathion	μg/l	USEPA 1657	190	< 0.03			
xvi.	Methyl Parathion	µg/l	USEPA 1657	0.3	< 0.03			
cvii.	Monocrotophos	μg/l	USEPA 1657	1	< 0.03			
viii.	Phorate	µg/l	USEPA 1657	2	< 0.03			

NOTES: Please see watermark "Original Test Report" to confirm the authenticity of this report. Results shall be referred to tested sample(s) and applicable to tested parameters only. Test report shall not be reproduced except in full without prior written approval of Anacon Labs. Liability of Anacon Labs is limited to invoiced amount only. Non-perishable and perishable sample(s) shall be disposed off after 30 days and 15 days respectively from the date of issue of Test Report, unless specified otherwise. #Permissible limit in absence of an alternate source for drinking water. MPN indicates most probable number. Imagin is equivalent to "ppm". "ug/l" is equivalent to "ppm". Indicates detection limit of instrument/method and shall be considered as "absent". ND-Not detected. Result for test no. 7 is not relevant.

REMARKS: Based upon request of the party, sample was tested for above mentioned parameters only. Sample complies with IS:10500:2012, for test conducted, indicating that it is fit for drinking purpose with respect to tested parameters.



Details of Salient Features

Table 9

Report on Soil Analysis, Kudag Sampling Duration: Post-Monsoon Sample Location: (Old Kudag/Mining Area)

S.N.	Test Parameter	Measurement Unit	Test Method	Test Resu
1	Infiltration rate	mm/hr	ASTMD 3385	100 May 100 Ma
2	Bulk density	g/cm ³	IS 2720 (Part 29)	19.27
3	Water holding capacity	%	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of	24,52
4	Particle size distribution		India)	1
	Sand	%	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India	32,64
	Silt	%	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India	28.16
	Clay	%	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India	39.2
5	Texture		Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India	Clay Loam
6	pH (1:2.5 Aq. Extract) at 25°C		Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	7.92 at 25°C
7	Electrical Conductivity (1:2.5 Aq. Extract)	μs/cm	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	416.7
8	Water soluble Calcium (as Ca)	mg/K.g	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	516.28
9	Water soluble Magnesium (as Mg)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	147.39
10	Water soluble Sodium (as Na)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	182.54
11	Water soluble Potassium (as K)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	38.2
12	Water soluble Chloride (as Cl)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	459.16
13	Water soluble Sulphate (as SO ₄)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	182.72
4	Exchangeable Sodium (as Na)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	86.24
5	Exchangeable Potassium (as K)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	16.52
6	Exchangeable Calcium (as Ca)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	252.81
7	Exchangeable Magnesium (as Mg)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	73.98
8	Sodium adsorption ratio	-	By Calculation	11.2
9	Total Organic matter	%	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of	0.87



Details of Salient Features

S.N.	Test Parameter	Measurement Unit	Test Method	Test Result
20	Total Organic Carbon	%	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	0.46
21	Available Nitrogen (as N)	Kg/hec	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	121.59
22	Available Phosphorous (as P)	Kg/hec	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	7.16
23	Available Potassium (as K)	Kg/hec	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	569.27
24	CEC	meq/100g	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	12.4
25	Arsenic (As)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent
26	Boron (B)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	0.14
27	Cadmium (Cd)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent
28	Chromium (Cr)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent
29	Copper (Cu)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	3.17
30	Lead (Pb)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent
31	Nickel (Ni)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent
32	Cobalt (Co)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	0.18
33	Iron (Fe)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	7.17
34	Manganese (Mn)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	16.28
35	Zine (Zn)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	0.39
36	Selenium (Se)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent

Note: 1. Results relate to tested sample only. **2.** Test report should not be reproduced partially. **3.** 'mg/Kg' is equivalent to 'ppm'. **4.** 'g/100g' is equivalent to '%w/w'. **5.** All parameters are in 1:5 water extract.

REMARKS: Based upon request of party, sample was tested for above mentioned parameter only.






Fig 5: Sampling Locations for Water