Environmental Status Report For Tatijharia Bauxite Mine at

Post & Teh.: Samri, (Kusmi)

Dist: Balrampur-Ramanujganj(C.G.)

Duration: October-November-December-2019

Name of Industry:-



M/s. Hindalco Industries Limited.,

Name of Laboratory:-



QCI-NABET Accredited EIA Consultant
MoEF&CC (GOI) and NABL Recognized Laboratory
ISO 9001:2015, ISO 14001:2015, OHSAS 18001:2007

60, Bajiprabhu Nagar, Nagpur - 440 033, MS Lab. & Consultancy: FP-34, 35, Food Park, MIDC, Butibori, Nagpur – 441122 Ph.: (0712) 2242077, 9373287475

Email: info@anacon.in, ngp@anacon.in website: www.anaconlaboratories.com

Rupambulti

Agent of Mines
Sama Mines Division
Hipdalco Industries Ltd

Foreword

The protection of environment plays a crucial role in maintaining the local environment quality for any mining industry. Hence compliance of the statutory requirements becomes very important to conserve the ecological balance within and surrounding the mine area. Therefore, environment protection is becoming a prerequisite for sustainable development. In line with this requirement, the management of M/s Hindalco Industries Ltd. has adopted a corporate responsibility of environment protection.

In order to comply with the Environment protection act, to fulfill statutory requirement and to be in tune with Environmental Preservation and sustainable development, M/s Hindalco Industries Ltd. has retained ANACON LABORATORIES PVT. LTD., Nagpur as Environment Consultants and for various Environmental issues related to their mines.

This report presents the Environmental Status for the period October-2019 to December-2019 as compliance to the statutory requirements.

The co-operation extended by the Staff and Management of M/s Hindalco Industries Ltd. during the work execution period is gratefully acknowledged.

For ANACON LABORATORIES PVT, LTD.

Place: Nagpur

Date: December, 2019



Introduction

1.1 Introduction

Hindalco Industries Limited (Hindalco) is one among the flagship companies of the Aditya Birla Group of Industries and is one of the largest corporate groups in India. This group is a leading manufacturer of Aluminum in India, having integrated facilities encompassing bauxite, mining, refining and smelting to achieve Aluminum.

Various processing units of Hindalco are strategically located in different parts of the nation to achieve optimum benefits. Over the past few decades the group has grown multifold in its production capacities, product mix and diversification in mining. The Chhattisgarh Environment Conservation Board (CECB) granted permission for establishing the Bauxite mine to Hindalco at block Tatijharia, Kudag and Samri mines in Balrampur District of Chhattisgarh State.

HINDALCO INDUSTRIES LTD. awarded the work to M/s ANACON LABORATORIES PVT. LTD. NAGPUR (ALPL) for carrying out monitoring of parameters for assessing pollution levels and preparation of monthly report (October-November-December-2019) as per the requirement of Chhattisgarh Environment Conservation Board (CECB) and Ministry of Environment Forest and climate change (MoEFCC) for Tatijharia mining lease in Balrampur District, Chhattisgarh State.

1.2 Background Information of Tatijharia Mine

Hindalco was granted Tatijharia Bauxite mining lease over an area of 1218.762hec.inTatijharia, Post Jamira, Tehsil Samri of Balrampur district, Chhattisgarh on 25/06/1998 for a period of 20 years. As per the Mines and Mineral (Development and Regulation) Amendment Act, 2015, Tatijharia lease has been extended up to 30 years i.e 24/06/2048. The mining operations were started on 01/04/2004. The production capacity of bauxite is 4.0 Lakh Tonnes Per Annum (LTPA).



Details of Salient Features

1.3 Salient Features of Tatijharia Bauxite Mine

The deposits occur in Tatijharia block, Post Jamira Tehsil Samri of Balrampur district. This deposit has been identified as one of the resources to cater the raw material requirements of the Hindalco Alumina refinery at Renukoot, Uttar Pradesh. The salient features of the project are presented below: (Table-1)

<u>Table 1</u>
<u>Salient Features of Tatijharia Bauxite Mines</u>

S.No.	Particulars	Details				
1.	Survey of India Toposheet No.	64 M /15				
2.	Latitude	23° 21′ 02″N to 23° 24′ 15″N				
3.	Longitude	83° 54′ 50″E to 83° 56′ 30″E				
4.	Elevation	1282-m above Mean Sea Level				
5.	Climatic Conditions (as per IMD, Ambikapur)	Annual maximum temperature: 30.3°C Annual minimum temperature: 17.7°C Average annual rainfall: 1401.1 mm				
6.	Mining lease area	1218.762hec.				
7.	Method of mining	Open cast (Semi-Mechanized)				
8.	Mode of transportation	Trucks				
9.	Land use	Agricultural and Barren land				
10.	Nearest Road	Samri to Kusmi (17 km)				
11.	Nearest Airport	Ranchi (143.56 km, E)				
12.	Nearest Town	Ambikapur (127 km, SW)				

1.4 Environmental Monitoring

Regular monitoring of environmental parameters is of immense importance to assess the status of environment during mining operation. With the knowledge of baseline conditions, the monitoring program will serve as an indicator for any deterioration in environment conditions due to mining operation of the project. Suitable mitigation steps will be taken in time to safeguard the environment, based on monitoring reports. Monitoring is important in the control of pollution since the efficiency of control measures can only be determined by monitoring.

In order to find out impact of mining activity on sensitive receptors, it is necessary to monitor Environmental Quality to know ground level concentrations of pollutants within and around the mining lease area, accordingly Hindalco Industries through ALPL has been monitoring at the following locations air, water and Noise quality on monthly basis during these months (Table 2).



Details of Salient Features

1.5 Air Environment

1.5.1 Ambient Air Quality Monitoring

Ambient Air Quality monitored at 8 locations in the core zone and buffer zone with reference to Tatijharia mine lease area shown in (Fig. 1).

Table 2 Locations of Ambient Air Quality Monitoring (AAQM) (1218.762 hec.)

SI. No.	(Core Zone)	SI. No.	Buffer Zone
1	Piprapat/Nr.Mining Area	5	Kutku Village/Nr.V.T.Center
2	Betpani	6	Sairaidh Campus
3	Virhorepat	7	Rajendrapur/Nr.Mining Area
4	Tatijharia Village/Nr.Weigh Bridge	8	Dumerkholi/Nr.Mining Area

The sampling stations are selected at the above mentioned locations, in downwind and upwind directions of the mining site in the core zone and buffer zone. ALPL is carrying out regular monitoring for PM₂₀, PM_{2.5}, SO₂, NO_X and Pb, Hg, As and Cr above Ambient Air Quality Monitoring (AAQM) locations. The dust fall rate was measured in the mining area (BKB campus) and Tatijharia village during Octoberl-2019 to December-2019. The AAQM sampling sites are selected considering seasonal variation in wind speed and wind direction.

1.5.2 Sampling Duration and Frequency

Ambient air quality monitoring was carried out for the parameters PM_{10} , $PM_{2.5}$, SO_2 , NOx and Pb, Hg, As and Cr from Octoberl-2019 to December-2019 as per CPCB norms.

Data is compared with the present revised standards mentioned in the latest Gazette Notification of the Central Pollution Control Board (CPCB) (November-18, 2009), and as per consent conditions mentioned in consent letter.



Details of Salient Features

1.5.3 MONITORED PARAMETERS AND FREQUENCY OF SAMPLING

Methods and Instruments used for Sampling

The air samples were analyzed as per methods specified by Central Pollution Control Board (CPCB).

The levels of Particulate Matter (PM₁₀), Sulphur Dioxide (SO₂,), Oxides of Nitrogen (NO_x), Pb, Hg, As and Cr were monitored for establishing the baseline status. PM₁₀ was collected with the help of Respirable particulate sampler operating 24 hours by drawing air which passes through the cyclone at the rate of 1.0 -1.3 m³/min which collects the particles less than 10 µm diameter over glass fiber filter paper. The dust deposited over the filter paper is measured as PM₁₀ and the smaller particulates from PM_{2.5}arecollected into the membrane filter paper. The dust fall rate was measured using dust fall jar. The jar was exposed for one month in the mining area and (BKB campus) Tatijharia village during April-2019 to June-2019. The jar was filled with 2 lit of distilled water. The water in the jar is mixed with copper sulphate solution (0.02 N solutions) to prevent any growth of algae. The water level in the jar is constantly maintained in such a way that 2 lit of water is always retained. The measurement techniques used for various pollutants and other details are given in (Table 3).

Table 3

MONITORED PARAMETERS AND FREQUENCY OF SAMPLING

Parameters	Sampling frequency				
Suspended Particulate Matter	24 hourly sample twice a week for Three months				
Respirable Particulate Matter	24 hourly sample twice a week for Three months				
Particulate Matter 2.5	24 hourly sample twice a week for Three months				
Sulphur dioxide (So2)	24 hourly sample twice a week for Three months				
Oxides of Nitrogen (NOx)	24 hourly sample twice a week for Three months				
Pb,Hg,As,Cr	8 hourly samples for 24 hour twice a week for three months				



Details of Salient Features

Table 4.0 Measurement Techniques for various pollutants

Sr. No.	Parameter	Technique	Technical Protocol	Minimum Reportable Value(µg/m³)	
1.	Suspended Particulate Matter	Respirable Dust Sampler (Gravimetric Method)	IS-5182 (Part - 23)		
2.	Respirable Particulate Matter	Respirable Dust Sampler (Gravimetric Method)	IS-5182 (Part-23)	5	
3.	Particulate Matter 2.5			5	
4.	Sulphur Dioxide	Modified West and Gaeke	IS-5182 (Part - II)	4	
5.	Oxide of Nitrogen	Jacob &Hochheiser Method	IS-5182 (Part - VI)	4	
6.	Pb, As,Hg, Cr	Acid Digestion Method	EPA Method	0.1	
7.	Dust Full	Gravimetric	IS-5182 (Part-I)		



Details of Salient Features

1.6 Meteorology: Wind Pattern

Meteorology: Wind Pattern

The data of wind pattern collected during the study period (April-May-June 2019) indicates that the wind was blowing predominately from (SW and SSW) directions, during study period.

Table 5.0

Wind Frequency Distribution Data

Sr. No.	Directions / Wind Classes (m/s)	0.5 - 2.1	2.1 - 3.6	3.6 - 5.7	5.7 -8.8	8.8 11.1	>= 11.1	Total (%)	
1	348.75 - 11.25	0.004082	0.008163	0.000000	0.000000	0.000000	0.000000	0.012245	
2	11.25 - 33.75	0.019048	0.008163	0.001361	0.000000	0.000000	0.000000	0.028571	
3	33.75 - 56.25	0.034014	0.012245	0.000000	0.000000	0.000000	0.000000	0.046259	
4	56.25 - 78.75	0.029932	0.019048	0.000000	0.000000	0.000000	0.000000	0.048980	
5	78.75 - 101.25	0.019048	0.004082	0.000000	0.000000	0.000000	0.000000	0.023129	
6	101.25 - 123.75	0.061224	0.006803	0.000000	0.000000	0.000000	0.000000	0.068027	
7	123.75 - 146.25	0.051701	0.002721	0.000000	0.000000	0.000000	0.000000	0.054422	
8	146.25 - 168.75	0.068027	0.001361	0.000000	0.000000	0.000000	0.000000	0.069388	
9	168.75 - 191.25	0.118367	0.002721	0.000000	0.000000	0.000000	0.000000	0.121088	
10	191.25 - 213.75	0.115646	0.001361	0.000000	0.000000	0.000000	0.000000	0.117007	
11	213.75 - 236.25	0.089796	0.005442	0.000000	0.000000	0.000000	0.000000	0.095238	
12	236.25 - 258.75	0.058503	0.014966	0.000000	0.000000	0.000000	0.000000	0.073469	
13	258.75 - 281.25	0.055782	0.012245	0.001361	0.000000	0.000000	0.000000	0.069388	
14	281.25 - 303.75	0.039456	0.014966	0.004082	0.000000	0.000000	0.000000	0.058503	
15	303.75 - 326.25	0.019048	0.035374	0.001361	0.000000	0.000000	0.000000	0.055782	
16	326.25 - 348.75	0.031293	0.009524	0.000000	0.000000	0.000000	0.000000	0.040816	
	Sub-Total	0.814966	0.159184	0.008163	0.000000	0.000000	0.000000	0.980978	
	Calms							0.017663	
	Missing/Incomplete								
	Total								

Summary of Wind Pattern

Season	First Predominant Wind Direction	Second Predominant Wind Direction	Calm Condition
October-November- December-2019	S (12.1%)	SW (11.7%)	1.7%




Figure.01: Wind Rose Diagram (Oct-Nov-Dec-2019)




Figure.02: Wind Class Frequency Distribution (Oct-Nov-Dec-2019).



Details of Salient Features

Table 6

Statistical Analysis

Location	Month & Year	PM-10 (μg/m ³)	PM-2.5 (µg/m ³)	SO ₂ (μg/m ³)	NO ₄ (μg/m ³)	Pb (μg/m ³)	Hg (μg/m ³)	As (ng/m ³)	Cr (µg/m ³)
Core Zone				Michigan				rnmi))See m	7.10.10
Tatijharia	Oct-2019	61.2	22.7	7.9	19.3	0.026	ND	ND	ND
Village/ Nr.Weigh	Nov-2019	65.5	33.4	12.2	25.4	0.025	ND	ND	ND
Bridge	Dec-2019	64,2	24.7	9.3	21.6	0.020	ND	ND	ND
	Oct-2019	66,2	25.0	9.8	25.9	0.031	ND	ND	ND
Piprapat/Nr. Mining Area	Nov-2019	59.9	26.8	8.9	19.9	0.032	ND	ND	ND
Mining Area	Dec-2019	67.8	26.3	10.2	23.1	0.013	ND	ND	ND
Mark Sept	Oct-2019	62.4	18.1	6.9	20.6	0.019	ND	ND	ND
Virhorepat	Nov-2019	56.0	20.5	8.3	18.2	0.023	ND	ND	ND
	Dec-2019	57.9	20.8	8.5	19.5	0.019	ND	ND	ND
	Oct-2019	56.5	16.9	7.2	18.8	0.017	ND	ND	ND
Betpani	Nov-2019	63.6	24.0	10.1	22.0	0.019	ND	ND	ND
	Dec-2019	63.2	25.8	9.7	21.3	0.015	ND	ND	ND
CPCB Star	ndards	100 (24 hrs)	60 (24 hrs)	80 (24 hrs)	80 (24 hrs)	1.0 (24 hrs)	-	6.0 (annual)	
Minim	um	56.0	16.9	6.9	18.2	0.013	***	***	-
Maxim	um	67.8	33.4	12.2	25.9	0.032	222		1
Avera	ge	62.0	23.8	9.1	21.3	0.022	Hee		***
98%	e	67.4	31.9	11.8	25.8	0.032	575		W

- The Average Concentration of PM10 within the Core Zone of Tatijharia Lease is 62.0 µg/m³.
- The Average Concentration of PM25 within the Core Zone of Tatijharia Lease is 23.8 µg/m³.
- The Average Concentration of SO₂ within the Core Zone of Tatijharia Lease is 9.1 µg/m³.
- The Average Concentration of NOx within the Core Zone of Tatijharia Lease is 21.3 μg/m³.
- The Average Concentration of Pb within the Core Zone of Tatijharia Lease is 0.022 µg/m³.

Conclusion: The Average Concentration within the Core Zone of Tatijharia Lease during this period (October-November-December-2019). It is within permissible limits as per CPCB Standards.



Details of Salient Features

Location	Month & Year	PM-10 (µg/m ³)	PM-2.5 (μg/m ³)	SO ₂ (μg/m ⁻³)	NO ₃ (μg/m ³)	Pb (μg /m ³)	Hg (μg/m ³)	As (ng/m ³)	Cr (µg/m ³)
Buffer Zone			Survivosaine,						101021111111
Kutku	Oct-2019	59.8	23.9	7.6	17.9	0.019	ND	ND	ND
Village/Nr.V.	Nov-2019	57.0	22.5	7.1	17.9	0.017	ND	ND	ND
T.Center	Dec-2019	62.4	22.7	8.6	19.3	0.015	ND	ND	ND
Sairaidh	Oct-2019	54.6	21.7	7.6	18.3	0.017	ND	ND	ND
Campus	Nov-2019	61.7	23.2	9.4	20.6	0.020	ND	ND	ND
	Dec-2019	67.7	24.7	8.2	18.5	0.018	ND	ND	ND
Rajendrapur/	Oct-2019	56.1	20.1	8.5	18.5	0.021	ND	ND	ND
Nr.Mining	Nov-2019	60.6	21.6	8.4	23.7	0.024	ND	ND	ND
Area	Dec-2019	59.4	21.2	7.9	17.6	0.017	ND	ND	ND
Dumerkholi/	Oct-2019	63.9	27.9	9.7	20.5	0.018	ND	ND	ND
Nr.Mining	Nov-2019	62.4	23.7	8.8	21.1	0.021	ND	ND	ND
Area	Dec-2019	58.0	18.4	7.4	20.1	0.020	ND	ND	ND
CPCB Star	ndards	100 (24 hrs)	60 (24 hrs)	80 (24 hrs)	80 (24 hrs)	1.0 (24 hrs)	100	6.0 (annual)	
Minim	um	54.6	18.4	7.1	17.6	0.015	222	***	1444
Maxim	um	67.7	27.9	9.7	23.7	0.024	****	***	
Avera	ge	60.3	22.6	8.3	19.5	0.019		777	8 444
98%	le	66.9	27.2	9.6	23.1	0.023		***	***

- The Average Concentration of PM10 within the Buffer Zone of Tatijharia Lease is 60.3 μg/m³.
- The Average Concentration of PM23 within the Buffer Zone of Tatijharia Lease is 22.6 µg/m³.
- The Average Concentration of SO2 within the Buffer Zone of Tatijharia Lease is 8.3 µg/m³.
- The Average Concentration of NOx within the Buffer Zone of Tatijharia Lease is 19.5 µg/m³.
- The Average Concentration of Pb within the Buffer Zone of Tatijharia Lease is 0.019 μg/m³.

Conclusion: The Average Concentration within the Buffer Zone of Tatijharia Lease during this period (October-November-December-2019). It is within permissible limits as per CPCB Standards.



Details of Salient Features

Month-wise Summary of Statistical Analysis

Tatijharia Lease (Core Zone):-

1.7 Ambient Air Quality:

Ambient air quality has been generated as per NAAQS 2009 for the month of October-November-December-2019. PM₁₀, PM_{2.5}, SO₂ & NO_X, The values obtained were then compared vis-a-vis the standards prescribed by CPCB for Industrial/ Rural / Residential uses.

1.7.1 Presentation of Results:

The summary of Ambient Air Quality monitoring results from October-2019 to December-2019 are presented in detail in Table 4.0. 98th percentile, maximum and minimum values etc. have been computed from the collected raw data for all the AAQ monitoring station. The data has been compared with the standards prescribed by Central Pollution Control Board (CPCB)/NAAQS for residential and rural zone.

A. Particulate Matter-PM₁₀:

The minimum and maximum concentrations for Particulate Matter-PM₁₀ were recorded as 56.0µg/m³ and 67.8µg/m³ at Virhorepat and Piprapat/Nr. Mining area respectively. The average concentration of PM₁₀ was 62.0µg/m³.

B. Particulate Matter-PM_{2.5}:

The minimum and maximum concentrations for Particulate Matter-PM_{2.5} were recorded as 16.9μg/m³ & 33.4μg/m³ at Betpani and Tatijharia Village/Nr. Weigh Bridge respectively. The average concentration of PM_{2.5} was 23.8μg/m³.

C. Sulphur Dioxide (SO₂):

The minimum and maximum for SO₂ concentrations were recorded as 6.9µg/m³ and 12.2µg/m³ respectively. The minimum concentration was recorded at Virhorepat and maximum concentration was also recorded at Tatijharia Village/Nr. Weigh Bridge. The average concentration SO₂ was 9.1µg/m³.

D. Nitrogen Oxide (NO_x):

The minimum and maximum for NO_X concentrations were recorded as $18.2\mu g/m^3$ and $25.9\mu g/m^3$. The maximum concentration was recorded at Piprapat/Nr. Mining area and the minimum concentration was recorded at Virhorepat. The average concentration of NO_X was $21.3\mu g/m^3$.



Details of Salient Features

E. Lead (Pb):

Maximum Lead detected in PM₁₀ samples was 0.032µg/m³ at Piprapat Village/Nr. Mining area and the minimum lead in PM₁₀ sample was 0.013/m³ also detected at Piprapat Village location.

No lead could be detected in PM_{2.5} samples at any of the Ambient Air samples at any of the locations.

F. Mercury (Hg):

Mercury was not detected at any of the locations in PM₁₀ samples as well as PM_{2.5} Samples.

G. Arsenic (As):


Arsenic was not detected at any of the locations in PM₁₀ samples as well as PM_{2.5} Samples.


H. Chromium (Cr):


Chromium was not detected at any of the locations in PM₁₀ samples as well as PM_{2.5} Samples.



Details of Salient Features












Details of Salient Features









Details of Salient Features

Tatijharia Lease (Buffer Zone):-

1.8 Ambient Air Quality:

Ambient air quality has been generated as per NAAQS 2009 for the month of October-November-December-2019. PM₁₀, PM_{2.5}, SO₂ & NO_x, the values obtained were then compared vis-a-vis the standards prescribed by CPCB for Industrial/ Rural / Residential uses.

1.8.1 Presentation of Results:

The summary of Ambient Air Quality monitoring results from October-2019 to December-2019 are presented in detail in Table 4.0. 98th percentile, maximum and minimum values etc. have been computed from the collected raw data for all the AAQ monitoring station. The data has been compared with the standards prescribed by Central Pollution Control Board (CPCB)/NAAQS for residential and rural zone.

I. Particulate Matter-PM₁₀:

The minimum and maximum both concentrations for Particulate Matter-PM₁₀ were recorded as 54.6µg/m³ and 67.7µg/m³ at Sairaidh Campus respectively. The average concentration of PM₁₀ was 60.3µg/m³.

J. Particulate Matter-PM2 5:

The minimum and maximum both concentrations for Particulate Matter-PM_{2.5} were recorded as 18.4μg/m³ & 27.9μg/m³ at Dumerkholi village location. The average concentration of PM_{2.5} was 22.6μg/m³.

K. Sulphur Dioxide (SO₂):

The minimum and maximum for SO_2 concentrations were recorded as $7.1\mu g/m^3$ and $9.7\mu g/m^3$ respectively. The minimum concentration was recorded at Kutku Village and maximum concentration was also recorded at Dumerkholi village location. The average concentration of SO_2 was $8.3\mu g/m^3$.

L. Nitrogen Oxide (NO_x):

The minimum and maximum both concentrations for NO_X were recorded as $17.6\mu g/m^3$ and $23.7\mu g/m^3$ at Rajendrapur/Nr. Mining Area location. The average concentration of NO_X was $19.5\mu g/m^3$.



Details of Salient Features

M. Lead (Pb):

Maximum Lead detected in PM₁₀ samples was 0.024µg/m³ at Rajendrapur/Nr. Mining Area and the minimum lead in PM₁₀ sample was 0.015/m³ detected at Kutku Village location.

No lead could be detected in PM_{2.5} samples at any of the Ambient Air samples at any of the locations.

N. Mercury (Hg):

Mercury was not detected at any of the locations in PM₁₀ samples as well as PM_{2.5} Samples.

O. Arsenic (As):


Arsenic was not detected at any of the locations in PM₁₀ samples as well as PM_{2.5} Samples.


P. Chromium (Cr):


Chromium was not detected at any of the locations in PM₁₀ samples as well as PM_{2.5} Samples.



Details of Salient Features












Details of Salient Features









Details of Salient Features

1.9 Noise Environment

The Director General of Mines Safety in its circular No. DG (Tech)/18 of 1975, has prescribed the noise level in mining occupations (TLV) for workers, in an 8 hour shift period with unprotected ear as 90 dB(A) or less. There will be some noise sources in mines, which produce noise levels above 90 dB(A), however, the workers are not expected to be exposed continuously for 8 hours. In order to maintain this statutory requirement Noise monitoring has been carried out in and around the mining lease area.

Work zone noise level in the mining area shall increase due to blasting excavation and transportation. The impacts due to the mining activities on the noise levels shall be negligible if all the precautions for the elimination of the noise are taken. The mining activities will be undertaken during daytime only. The daytime equivalent noise levels, when all the machineries are in operation, shall be minimized as the machineries have been provided with noise control equipment. Noise monitoring carried out on monthly basis at eight locations namely core and buffer zone.

Identification of sampling locations

Noise at different noise generating sources has been identified based on the activities in the village area and ambient noise due to traffic.

The noise monitoring has been conducted for determination of ambient noise levels in the mining area and villages. The noise levels at each location were recorded for 24 hours.

Method of Monitoring

Sound Pressure Level (SPL) measurements were monitored at eight locations. The readings were taken for every hour for 24 hours. The day noise levels have been monitored during 6 am to 10 pm and night levels during 10 pm to 6 am at eight locations within 10-km radius of the study area.

Noise level monitoring was carried out continuously for 24 hours with one hour interval starting at 06.00 hrs to 06.00 hrs next day.

Noise levels monitored during day and night at 8 locations are found to be below the stipulated standard of CPCB as for Industrial area as 75dB(A) and 70dB(A) for day and night respectively as given in (Table 7).



Details of Salient Features

Instrument used for monitoring

Noise levels were measured using integrated sound level meter Model no. HTC-SL-1352. This instrument is capable of measuring the Sound Pressure Level (SPL), Leq.

Table 7

Noise Emission Monitoring Report

SR. NO. LOCATION Month Noise-dB(A)										
SK. NO.	LOCATION	Month	Day Time	Night Time						
Core Zone										
	m	October-2019	63.7	50.8						
1.	Tatijharia Village/Nr.Weigh Bridge	November-2019	62.7	52.5						
	Bridge	December-2019	59.4	47.2						
	and Bullet Tarana and a super-	October-2019	59.2	47.6						
2.	Piprapat/Nr. Mining Area	November-2019	56.4	45.2						
		December-2019	57.1	46.5						
Buffer Zoi	ne promote de la companya de la comp									
	Samri-	October-2019	61.5	48.2						
1.	Gopatu/ Near Weigh bridge	November-2019	62.1	49.6						
	Gopatu/ Near Weigh bridge	December-2019	61.6	48.7						
		October-2019	56.8	45.6						
2.	Rajendrapur/Nr.Mining Area	November-2019	53.7	42.4						
		December-2019	54.9	43.8						
CPCB Stan	dards									
Industrial /	Area		75	70						
Residential	area		55	45						

<u>Conclusion</u>:- The Noise Monitoring Results at Tatijharia Lease during this period (October-November-December-2019), it is within permissible limits as per CPCB Standards.

Table 8
HEMM Spot Noise Level Monitoring

SI. No.	Location	October- 2019		November- 2019		December- 2019	
		Min.	Max.	Min.	Max.	Min.	Max.
1.	Piprapat/Nr.Mining Area	56.5	67.2	58.2	66.7	57.6	65.9
2.	Tatijharia Village/ Nr.Weigh Bridge	58.7	71.5	61.5	73.2	62.3	72.4



Details of Salient Features

2.0 Water Quality

The existing status of water quality for ground water and surface water was assessed by collecting the water samples from underground wells from the piprapat/Nr.mining area.

The purpose of the study is to assess the water quality characteristics for critical parameters, evaluate the impacts on agricultural productivity, habitat conditions, recreational resources and aesthetics in the vicinity and identification of impact on water quality by this project and related activities.

The physico-chemical analysis of water samples collected during the study period is given in **(Table-9 and Fig.5)**. The overall water quality found to be below the stipulated standards of IS 10500-2012 for ground water & found to be fit for drinking purpose for tested parameters. Thus the impacts due to mining activities have been found to be insignificant.

The drinking water is supplied by the tankers from for-away sources. Hence, additional care now be taken to chlorinate the tankers before leaving the supply source.



Details of Salient Features

Table 9

Report on Chemical Examination of Ground Water (Average of Three Months October-November-December-2019)

Location: GW1) Piprapat/Near Mining Area
Sample Source:-Borewell Water

TEST RESULTS

			Test Method		10500 : 2012 r - Specification)	T-11 P-11
Sr. No.	Test Parameter	Measurement Unit	Test medido	Acceptable Limit	*Permissible Limit	Test Result
1.	pH value		IS 3025 (Part 11)	6.5 to 8.5	No relaxation	7.64 at 25°C
2.	Turbidity	NTU	IS 3025 (Part 10)	1	5	0.3
3.	Colour	Hazen units	IS 3025 (Part 4)	5	15	10
4.	Odour		IS 3025 (Part 5)	Agreeable	Agreeable	Agreeable
5.	Taste		IS 3025 (Part 8)	Agreeable	Agreeable	Agreeable
6.	Iron (as Fe)	mg/l	IS 3025 (Part 2)	1.0	No relaxation	0.21
7.	Free residual chlorine	mg/l	IS 3025 (Part 26)	Min. 0.2	1	< 0.1
8.	Total dissolved solids	mg/l	IS 3025 (Part 16)	500	2000	463
9.	Fluoride (as F)	mg/l	IS 3025 (Part 60)	1.0	1.5	0.47
10.	Cyanide (as CN)	mg/l	IS 3025 (Part 27)	0.05	No relaxation	< 0.005
11.	Chloride (as CI)	mg/l	IS 3025 (Part 32)	250	1000	48.59
12.	Total Alkalinity (as CaCO ₃)	mg/l	IS 3025 (Part 23)	200	600	116,28
13.	Total hardness (as CaCO ₃)	mg/l	IS 3025 (Part 21)	200	600	171.05
14.	Calcium (as Ca)	mg/l	IS 3025 (Part 40)	75	200	47.59
15.	Magnesium (as Mg)	mg/l	IS 3025 (Part 46)	30	100	12.68
16.	Sulphate (as SO ₄)	mg/l	IS 3025 (Part 24)	200	400	21,41
17.	Nitrate (as NO ₃)	mg/l	APHA Method	45	No relaxation	9.52
18.	Copper (as Cu)	mg/l	IS 3025 (Part 2)	0.05	1.5	< 0.03
19.	Manganese (as Mn)	mg/l	IS 3025 (Part 2)	0.1	0.3	< 0.05
20.	Mercury (as Hg)	mg/l	IS: 3025 (Part 48)	0.001	No relaxation	< 0.0005
21.	Cadmium (as Cd)	mg/l	IS: 3025 (Part 41)	0.003	No relaxation	< 0.001
22.	Selenium (as Se)	mg/l	IS: 3025 (Part 56)	0.01	No relaxation	< 0.001
23.	Arsenic (as As)	mg/l	IS: 3025 (Part 37)	0.01	No relaxation	< 0.01
24.	Aluminium (as Al)	mg/l	IS: 15302	0.03	0.2	< 0.005
25.	Lead (as Pb)	mg/l	IS: 3025 (Part 47)	0.01	No relaxation	< 0.001
26.	Zinc (as Zn)	mg/l	IS 3025 (Part 2)	5	15	1.1



Details of Salient Features

Sr.	Test Parameter	Measurement	Test Method		10500 : 2012 r - Specification)	Tool Decule					
No	rest Parameter	Unit	rest Method	Acceptable Limit	*Permissible Limit	Test Result					
27.	Nickel (as Ni)	mg/l	IS 3025 (Part 2)	0.02	No relaxation	< 0.01					
28.	Total Chromium (as Cr)	mg/l	IS 3025 (Part 2)	0.05	No relaxation	< 0.03					
29.	Barium (as Ba)	mg/l	Annexure F of IS 13428	0.7	No relaxation	< 0.01					
30.	Ammonia (as N)	mg/l	IS 3025 (Part 34)	0.5	No relaxation	< 0.1					
31.	Sulphide (as H ₂ S)	mg/l	IS 3025 (Part 29)	0.05	No relaxation	< 0.03					
32.	Chloramines (as Cl ₂)	mg/l	IS 3025 (Part 26)	4.0	No relaxation	< 0.05					
33.	Molybdenum (as Mo)	mg/l	IS 3025 (Part 2)	0.07	No relaxation	< 0.001					
34.	Silver (as Ag)	mg/l	Annexure J of IS 13428	0.1	No relaxation	< 0.001					
35.	Polychlorinated Biphenyls (PCB)	µg/l	USEPA 508	0.5	No relaxation	< 0.03					
36:	Boron (as B)	mg/l	IS 3025 (Part 2)	0.5	2.4	< 0.1					
37.	Mineral Oil	mg/l	IS 3025 (Part 39)	0.5	No relaxation	< 0.001					
38.	Tri Halo Methane										
	a. Bromoform			0.1	No relaxation	Absent					
	b. Dibromochloromethane		ADILA 6222	0.1	No relaxation	Absent					
	c. Bromodichloromethane	mg/l	APHA 6232	0.06	No relaxation	Absent					
	d.Chloroform		Market Name of the	0.2	No relaxation	Absent					
39.	Phenolic compounds (as C ₆ H ₅ OH)	mg/l	IS 3025 (Part 43) :1001	0.001	0.002	< 0.001					
40.	Anionic detergents (as MBAS)	mg/l	IS 13428:2005 (Annex K)	0.2	1.0	< 0.01					
41,	Polynuclear aromatic hydrocarbon (PAH)	µg/l	USEPA: 550	0.1	No relaxation	< 0.03					
42.	Total coliform	Per 100 ml	IS 15185	Absent	Absent	Absent					
43.	Escherichia coli	Per 100 ml	IS 15185 ; 2016	Absent	Absent	Absent					

Sr. No.	Test Parameter	Measurement Unit	Test Method	As per IS 10500 : 2012 (Drinking Water - Specification)	Test Result		
44.	Pesticides residues						
i.	Alpha-HCH	µg/l	USEPA 508	0.01	< 0.01		
ii.	Beta HCH	µg/l	USEPA 508	0.04	< 0.03		
Hi.	Delta- HCH	µg/l			< 0.03		
iv.	Alachlor	µg/l	USEPA 508	20 0.03	< 0.03 < 0.03		
V.	Aldrin / Dieldrin	µg/l	USEPA 508				
vi.	Atrazine	µg/l	USEPA 1657	2	< 0.03		
vii.	Butachlor	μg/l	USEPA 508	125	< 0.03		
viii.	Chlorpyrifos	µg/l	USEPA 1657	30	< 0.03		
ix.	DDT and its Isomers	µg/l	USEPA 508	1	< 0.03		
Χ.	Gamma - HCH (Lindane)	µg/l	USEPA 508	2	< 0.03		
xi.	2,4-Dichlorophenoxyacetic acid	µg/l	USEPA 1657	30	< 0.03		
xii.	Endosulphan	µg/l	USEPA 508	0.4	< 0.03		
xiii.	Ethion	µg/l	USEPA 1657	3	< 0.03		
xiv.	Isoproturon	µg/l	USEPA 1657	9	< 0.03		
XV.	Malathion	µg/l	USEPA 1657	190	< 0.03		
xvi.	Methyl Parathion	µg/l	USEPA 1657	0.3	< 0.03		
cvii.	Monocrotophos	µg/l	USEPA 1657	1	< 0.03		
Vili.	Phorate	µg/l	USEPA 1657	2	< 0.03		

NOTES: •Please see watermark "Original Test Report" to confirm the authenticity of this report. • Results shall be referred to tested sample(s) and applicable to tested parameters only. • Test report shall not be reproduced except in full without prior written approval of Anacon Labs. • Liability of Anacon Labs is limited to invoiced amount only. • Non-perishable and perishable sample(s) shall be disposed off after 30 days and 15 days respectively from the date of issue of Test Report, unless specified otherwise. • #Permissible limit in absence of an alternate source for drinking water. • MPN indicates most probable number. • 'mg/l' is equivalent to 'ppb'. • '< indicates detection limit of instrument/method and shall be considered as 'absent'. • Result for test no. 7 is not relevant.

REMARKS: Based upon request of the party, sample was tested for above mentioned parameters only. Sample complies with IS:10500:2012, for tests conducted, indicating that it is fit for drinking purpose with respect to tested parameters.



Details of Salient Features

Table 10

Dust fall Rate

Sr.No.	Location	December-2019	
U1.11U.	Location	Rate (MT/km²/Month)	
1.	Piprapat/Near Mining Area	21.84	



Details of Salient Features

Table 11

Soil Analysis Report Sampling Month: December-2019

Sampling Location: Tatijharia

S.N.	. Test Parameter	Measurement Unit	Test Method	Test Result		
1	Infiltration rate	mm/hr	ASTMD 3385	17.46		
2	Bulk density	g/cm ³	IS 2720 (Part 29)	1.327		
3	Water holding capacity	%	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	23.52		
4	Particle size distribution					
	Sand	%	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India	26,43		
	Silt	96	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India	23,5		
	Clay	%	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India	50.00		
5	Texture		Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India	Clay		
6	pH (1:2.5 Aq. Extract) at 25°C		Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	7.81 at 25°C		
7	Electrical Conductivity (1:2.5 Aq. Extract)	μs/cm	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	429.16		
8	Water soluble Calcium (as Ca)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	463.38		
9	Water soluble Magnesium (as Mg)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	113.52		
10	Water soluble Sodium (as Na)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	247.19		
11	Water soluble Potassium (as K)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	28.54		
12	Water soluble Chloride (as Cl)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	273.16		
13	Water soluble Sulphate (as SO ₄)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	349.28		
14	Exchangeable Sodium (as Na)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	127.39		
15	Exchangeable Potassium (as K)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	16.54		
16	Exchangeable Calcium (as Ca)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	212.62		
17	Exchangeable Magnesium (as Mg)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	61.73		
18	Sodium adsorption ratio		By Calculation	18.2		
19	Total Organic matter	%	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	1.69		
20	Total Organic Carbon	%	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	1.12		
21	Available Nitrogen (as N)	Kg/hec	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	257.39		
22	Available Phosphorous (as P)	Kg/hec	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	18.24		
23	Available Potassium (as K)	Kg/hec	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	616.52		
24	CEC	meq/100g	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	11.3		



Details of Salient Features

S.N. Test Parameter		Measurement Unit	Test Method	Test Result
25	Arsenic (As)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent
26	Boron (B)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	0.21
27	Cadmium (Cd)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent
28	Chromium (Cr)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent
29	Copper (Cu)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	1.56
30	Lead (Pb)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent
31	Nickel (Ni)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent
32	Cobalt (Co)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	0.24
33	Iron (Fe)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	7.62
34	Manganese (Mn)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	16.84
35	Zinc (Zn)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	1.21
36	Selenium (Se)	mg/Kg	Method Manual, Soil testing in India (Department of agriculture & corporation, Govt of India)	Absent

Note: 1. Results relate to tested sample only. 2. Test report should not be reproduced partially, 3. 'mg/Kg' is equivalent to 'ppm'. 4. 'g/100g' is equivalent to '%w/w'. 5. All parameters are in 1:5 water extract.

REMARKS: Based upon request of party, sample was tested for above mentioned parameters only.



Details of Salient Features




FIG 3: SAMPLING LOCATIONS FOR AIR, NOISE & SOIL



Details of Salient Features

