

**EVALUATION OF ENVIRONMENTAL PARAMETERS,  
COMPLIANCE AND RELATED ADVICE FOR KATHAUTIA  
OPEN CAST COAL MINES, DALTONGANJ, JHRKHAND**

(SUMMER SEASON & MONSOON SEASON)  
(APRIL, 2018 TO SEPTEMBER, 2018)

*Prepared  
For*



**M/s HINDALCO INDUSTRIES LIMITED  
Daltonganj-822101  
Jharkhand**

*Prepared  
by*



**ENVIRONMENTAL ASSESSMENT AND REMEDIATION  
(NREM)  
CSIR-CENTRAL INSTITUTE OF MINING & FUEL RESEARCH  
BARWA ROAD, DHANBAD - 826 015**

(OCTOBER-2018)

**Report**

On


**Evaluation of Environmental Parameters,  
Compliances and Related Advice for Kathautia  
Open Cast Coal Mines, Daltonganj, Jhrkhand**

(SUMMER SEASON & MONSOON SEASON)  
(APRIL, 2018 TO SEPTEMBER, 2018)

Project No.: SSP/310/2018-19


1. This report is meant for the internal use of your organisation only and it should not be published in full or part by your organisation or staff. It should not be communicated/circulated to outside parties except the concerned government department.
2. CSIR-Central Institute of Mining and Fuel Research, Dhanbad reserves the right to publish the results of research for the benefit of the industry.


**Signature of Project Proponent**

  
(Gautam Chandra Mondal)  
Principal Scientist  
Project Leader  
CSIR-CIMFR, Dhanbad

  
(K. K. K. Singh)  
Chief Scientist & HORG  
Project Co-ordinator  
CSIR-CIMFR, Dhanbad

**CSIR-CIMFR Authorised Signatories**

  
(V. K. Kalyani)  
Sr. Principal Scientist  
Project Monitoring  
CSIR-CIMFR, Dhanbad

  
(R. V. K. Singh)  
Chief Scientist & HORG  
Business Development & Industrial Liasion  
CSIR-CIMFR, Dhanbad

## **PROJECT PERSONNEL**

### **Project Co-coordinator**

Dr. K. K. K. Singh

### **Project Leader**

Dr. Gautam Chandra Mondal

### **Key Team Members**

Dr. Abhay Kr. Singh

Dr. Siddharth Singh

Ms Pallabi Das

Dr. B. Pandey

### **Team Members**

Dr. M. R. Mondal

Mr. S. Prasad

Mr. A. S. Kumar

## **CONTENTS**

<b>S.N.</b>	<b>DESCRIPTION</b>	<b>PAGE NO.</b>
1.0	Introduction	1
2.0	Mining Scenario	2
3.0	Environmental Scenario in the Mining Area	4
3.1	Air Environment	4
3.1.1	Source of Air Pollution	4
3.1.2	Methodology & Instruments Used	4
3.1.3	Air Quality	4
3.1.4	Results and Discussions	6
3.2	Water Environment	7
3.2.1	Sources of water Pollution	7
3.2.2	Instruments used	7
3.2.3	Water Quality of the Area	8
3.3	Noise Environment	16
3.3.1	Sources of Noise	16
3.3.2	Instruments used	16
3.3.3	Results and Discussions	17
4.0	Conclusion	20
5.0	Recommendations & Follow-up Action	20

## LIST OF TABLE

TABLE NO.	DESCRIPTION	PAGE NO.
1.	Methodology and Instrument Used for Air Quality Analysis	4
2.	Details of Sampling Locations	5
3.	Ambient Air Quality Report for Core Zone	5
4.	Ambient Air Quality Report for Buffer Zone	6
5.	Mine Discharge Water Quality Data (Summer Season)	10
6.	Ground Water Quality Data (Summer Season)	11
7.	Surface Water Quality Data (Summer Season)	12
8.	Mine Discharge Water Quality Data (Monsoon Season)	13
9.	Ground Water Quality Data (Monsoon Season)	14
10.	Surface Water Quality Data (Monsoon Season)	15
11.	Noise Generating Mining Equipments	16
12.	Noise Level in Core Zone of the Study Area (Summer Season)	17
13.	Noise Level in Buffer Zone of the Study Area (Summer Season)	18
14.	Noise Level in Core Zone of the Study Area (Monsoon Season)	18
15.	Noise Level in Buffer Zone of the Study Area (Monsoon Season)	20

## 1.0 INTRODUCTION

Mining is a site specific and ecologically sensitive industry. For sustaining national development, mining of coal and minerals is of paramount importance for developed as well as developing countries. To meet the energy requirements of the country, increased coal production has been possible due to large-scale surface mining activities. Surface mining causes environmental disturbance in the form of land degradation, removal of OB material stress on air and water regime and finally interferes in the balance of the ecosystem. To meet these problems, sound environmental management system for pre-mining, active mining and post mining stages in the form of Environmental Impact Assessment, Environmental Management Practice for concurrent mining and Environmental Audit has been made necessary by the regulating state and central authorities. Regular monitoring of the different components of environment is made necessary for evaluating the requirements of environmental management system and its impact in the society. This report presents such study conducted by CSIR-Central Institute of Mining and Fuel Research (CSIR-CIMFR), Dhanbad for **Kathautia Open Cast Coal Mine** belonging to **M/S Hindalco Industries Ltd, Daltonganj**.

### i) LOCATION

The lease area of KOCCM covers land in villages: Kathautia, Kajari, Garikhas, Palhekhurd, Sakhui, Sikka and Batsara in Patan and Pandwa Blocks of district Palamau (Jharkhand). Kathautia Open Cast Coal Mines (KOCCM), is located in southern boundary of the block is about 10 KM from Daltonganj. The project area is situated between the latitude 24<sup>0</sup> 07' 02" N and 24<sup>0</sup> 08' 52" N and longitude 84<sup>0</sup> 03' 42" E & 84<sup>0</sup> 06' 52" E. The site is well connected by road and 15 km away from Daltonganj. The project came into operation in the year 2008.

M/S Hindalco Industries Ltd, Daltonganj; approached CSIR-Central Institute of Mining and Fuel Research (CSIR-CIMFR), Dhanbad for doing the following work for one year i.e. 2018-2019.

- Environmental study of Air, Water, Soil, Noise, Flora & fauna of the core and buffer zone.
- The Environmental monitoring will be conducted on seasonal basis.
- Advice into the adoption of necessary control measures.
- Preparation of Environmental Statement as stipulated in consent to operate of JSPCB, Ranchi.

The detailed studies with respect to air, water and noise will be carried on seasonal basis in the year 2018-19 while soil samples, for the adjoining mining area, will be collected once in a year and analyzed in the CSIR-CIMFR laboratory.

## 2.0 (i) MINING SCENARIO

Presently the mine is not in operation. At KOCCM, Pandwa Top & Rajhara B seams have been worked out by opencast mining with shovel and dumper combinations. Shovels of different capacities such as 3.0 cubic meters, 2.7 cubic meters and 2.1 cubic meters are used along with 25 T Volvo Dumpers.

The coal seams in this OCP are as follows:

- |       |                 |    |                       |
|-------|-----------------|----|-----------------------|
| (i)   | Rajhara A seam  | -> | 0.4 – 2.67 mts thick  |
| (ii)  | Rajhara B seam  | -> | 0.42 – 2.60 mts thick |
| (iii) | Pandwa Top seam | -> | 0.25 – 3.11 mts thick |

The average grade of coal is 'B' & 'D'. The open cast mine is worked by Shovel-Dumper combination with an average stripping ratio of 1:9.66. OB was dumped outside the quarry during initial years. Till the bottom most seams are worked out and quarry

benches advance sufficiently, backfilling will be allowed and backfilling of Overburden has already been started.

The working area by opencast method is having the seams Pandwa Top, Rajhara B & Rajhara A. The grades of coal of the seams are mostly found as B & D. The total Block area of this block is approximately 938.27 ha out of which, 687.93 ha is granted for Mining Lease.

## (ii) REGIONAL GEOLOGY

The Daltonganj coalfield occupies an elongated area of 250 sq km along a narrow east west trend north of Daltonganj (24° 02' 00"; 84° 04' 00") and falls between latitude 24° 00' 00" and 24° 12' 00" N and longitudes 83° 59' 00" and 84° 15' 00" E. However, the lower Gondwana coal seams underlie only 95 sq km, the Talchir Formation occupying the entire remaining area. Sequence of Karharbari seam is given below:-

### SEQUENCE OF KARHARBARI COAL SEAMS, DALTONGANJ COALFIELD

S. N.	Particulars	Thickness range (meters)
1	<i>Major coal seams</i>	
	a) Top cover over Rajhara A seam	10.25 – 44.75
	Rajhara A seam	0.4 – 2.67
	b) Parting cover over Rajhara B seam	4.20 – 15.30
	Rajhara B seam	0.42 – 2.60
	(c) Parting cover over Pandwa Top seam	4.70 – 13.87
	Pandwa Top seam	0.25 – 3.11
2	<i>Gradient of strata (degree)</i>	1 in 22.16 (2° 35' 1.67")
3	Category of excavation :	
	(a) Weathered rock (cat)	
	(b) Overburden rock (cat)	
	(c) Coal (cat)	

### 3.0 ENVIRONMENTAL SCENARIO IN THE MINING AREA

#### 3.1 AIR ENVIRONMENT

##### 3.1.1 SOURCES OF AIR POLLUTION

Coal transportation, OB removal, drilling, blasting, haul road and movements of mining equipments are the major sources of air pollution in the area. Generally, dust generation is of major concern. NO<sub>2</sub> is liberated in the time of blasting and during the movement of mining machineries. This coal contains very less sulphur and as such the concentration of SO<sub>2</sub>. In Indian coal, it is low, except Assam where sulphur content is high.

##### 3.1.2 METHODOLOGY & INSTRUMENTS USED:

The methodology and instruments used for air quality monitoring and analysis are given in Table 1 as below:

Table 1: Methodology and Instrument Used for Air Quality Analysis

Parameters	Method	Instrument
PM <sub>2.5</sub>	IS-5182 (Part 23):2006 Gravimetric Method Beta attenuation Method	Fine Particulate Sampler
PM <sub>10</sub>	IS-5182 (Part 23):2006 Gravimetric Method Beta attenuation Method	Fine Particulate Sampler / Respirable Dust Sampler (RDS)
SO <sub>2</sub>	IS-5182 (Part 2):2001 (Improved West & Gaeke method)	Fine Particulate Sampler/RDS with gaseous attachment
NO <sub>x</sub>	IS-5182 (Part 6):2006 (Jacob & Hochheiser modified method)	Fine Particulate Sampler/RDS with gaseous attachment

##### 3.1.3 AIR QUALITY

Air quality monitoring in core and buffer zone of the Kathautia Open Cast mine has been carried out in summer season and monsoon season for the year 2018-19 to assess the impact of mining activities on the ambient air quality. During the study, two sampling locations for ambient air quality had been fixed in buffer zone and three in core zone area. Details of sampling stations along with the source of air pollution are given in Table 2.

The air quality at these locations is presented from Tables 3-4. The results show that the ambient air quality of the villages, in and around the mining site, is least affected as the mine is not in operation during the study period.

Table 2: Details of Sampling Locations

Stn. Code	Location	Source of Air Pollution
<b>CORE ZONE</b>		
CA <sub>1</sub>	Near Mine Site Office	Mining activity, Kachha road and vehicular movement.
CA <sub>2</sub>	Near Haul Road	Mining activity and vehicular movement.
CA <sub>3</sub>	Near Stockyard	Mining activity and vehicular movement.
<b>BUFFER ZONE</b>		
BA <sub>1</sub>	R. R. Colony	Household coal burning and vehicular movement, etc.
BA <sub>2</sub>	Batsara Village	Household coal burning and vehicular movement, etc.

Table 3: Ambient Air Quality Report for Core Zone

Sampling Code	Sampling Location	Season	Date of Sampling	Parameters (µg/m <sup>3</sup> )				Remarks
				PM <sub>2.5</sub>	PM <sub>10</sub>	SO <sub>2</sub>	NO <sub>2</sub>	
CA <sub>1</sub>	Near Mine Site Office	Summer	23/04/2018	49.8	85.7	25.4	37.4	
			12/06/2018	50.7	86.1	21.5	40.4	
		Monsoon	27/07/2018	33.1	50.0	10.2	12.4	Raining
			28/08/2018	38.1	54.8	11.8	14.2	Raining
CA <sub>2</sub>	Near Haul Road	Summer	23/04/2018	52.6	88.4	25.0	47.5	
			13/06/2018	56.5	85.0	23.3	46.3	
		Monsoon	28/07/2018	39.6	54.5	10.9	12.1	Raining
			28/08/2018	36.2	52.0	13.4	13.5	Raining
CA <sub>3</sub>	Near Stockyard	Summer	28/09/2018	44.3	60.4	18.1	33.6	
			24/04/2018	57.7	82.0	20.3	39.5	
		Monsoon	12/06/2018	55.4	76.6	22.7	43.5	
			27/07/2018	37.2	47.2	11.7	14.1	Raining
<b>Standards as per NAAQS-2009</b>				<b>60</b>	<b>100</b>	<b>80</b>	<b>80</b>	

**Table 4: Ambient Air Quality Report for Buffer Zone**

Sampling Code	Sampling Location	Season	Date of Sampling	Parameters ( $\mu\text{g}/\text{m}^3$ )				Remarks
				PM <sub>2.5</sub>	PM <sub>10</sub>	SO <sub>2</sub>	NO <sub>2</sub>	
BA <sub>1</sub>	R. R. Colony	Summer	24/04/2018	53.2	69.6	24.6	34.3	
			13/06/2018	51.2	68.8	26.6	32.5	
		Monsoon	29/07/2018	36.8	44.1	12.4	13.5	Raining
			29/08/2018	37.2	42.7	14.5	15.3	Raining
BA <sub>2</sub>	Batsara Village	Summer	25/04/2018	44.2	62.4	26.1	26.4	
			13/06/2018	49.2	63.9	23.8	29.7	
		Monsoon	28/07/2018	36.2	45.0	11.4	10.8	Raining
			29/09/2018	40.8	55.0	20.1	21.7	
<b>Standards as per NAAQS-2009</b>				<b>60</b>	<b>100</b>	<b>80</b>	<b>80</b>	

### 3.1.4 RESULTS AND DISCUSSIONS

During summer season (April to June), PM<sub>2.5</sub> concentration level at Near Mine Office in core zone varies from 49.8  $\mu\text{g}/\text{m}^3$  to 50.7  $\mu\text{g}/\text{m}^3$  and PM<sub>10</sub> from 85.7  $\mu\text{g}/\text{m}^3$  to 86.1  $\mu\text{g}/\text{m}^3$ . At Haul Road concentration level of PM<sub>2.5</sub> varies from 52.6  $\mu\text{g}/\text{m}^3$  to 56.5  $\mu\text{g}/\text{m}^3$  and PM<sub>10</sub> from 85.0  $\mu\text{g}/\text{m}^3$  to 88.4  $\mu\text{g}/\text{m}^3$ . Near Stockyard concentration level of PM<sub>2.5</sub> varies from 55.4  $\mu\text{g}/\text{m}^3$  to 57.7  $\mu\text{g}/\text{m}^3$  and PM<sub>10</sub> from 76.6  $\mu\text{g}/\text{m}^3$  to 82.0  $\mu\text{g}/\text{m}^3$ . In the core zone the PM<sub>2.5</sub> and PM<sub>10</sub> values are within the threshold value i.e. 60  $\mu\text{g}/\text{m}^3$  for PM<sub>2.5</sub> and 100  $\mu\text{g}/\text{m}^3$  for PM<sub>10</sub> as per the guideline of NAAQS around the entire sampling site. Concentration of SO<sub>2</sub> and NO<sub>2</sub> are also found within the limit of 80  $\mu\text{g}/\text{m}^3$  as per the guideline of NAAQS in all the sampling sites of core zone of the mine.

During summer, the PM<sub>2.5</sub> concentration at R. R. Colony in buffer zone is in the range of 51.2  $\mu\text{g}/\text{m}^3$  to 53.2  $\mu\text{g}/\text{m}^3$  and the concentration of PM<sub>10</sub> ranges from 68.8  $\mu\text{g}/\text{m}^3$  to 69.6  $\mu\text{g}/\text{m}^3$ . The PM<sub>2.5</sub> concentration at Batsara Village is in the range of 44.2  $\mu\text{g}/\text{m}^3$  to 49.2  $\mu\text{g}/\text{m}^3$  and the concentration of PM<sub>10</sub> ranges from 62.4  $\mu\text{g}/\text{m}^3$  to 63.9  $\mu\text{g}/\text{m}^3$ . In the buffer zone both the values are also within the threshold value i.e. 60  $\mu\text{g}/\text{m}^3$  for PM<sub>2.5</sub> & 100  $\mu\text{g}/\text{m}^3$  for PM<sub>10</sub> as per the guideline of NAAQS. Concentration of SO<sub>2</sub> and NO<sub>2</sub> are

also found within the limit 80  $\mu\text{g}/\text{m}^3$  as per the guideline of NAAQS in all the sampling sites of core zone of the mine.

During Monsoon season (July to September), PM<sub>2.5</sub> concentration level at Near Mine Office in core zone varies from 33.1  $\mu\text{g}/\text{m}^3$  to 41.7  $\mu\text{g}/\text{m}^3$  and PM<sub>10</sub> from 50.0  $\mu\text{g}/\text{m}^3$  to 62.2  $\mu\text{g}/\text{m}^3$ . At Haul Road concentration level of PM<sub>2.5</sub> varies from 36.2  $\mu\text{g}/\text{m}^3$  to 44.3  $\mu\text{g}/\text{m}^3$  and PM<sub>10</sub> from 52.0  $\mu\text{g}/\text{m}^3$  to 60.4  $\mu\text{g}/\text{m}^3$ . Near Stockyard concentration level of PM<sub>2.5</sub> varies from 37.2  $\mu\text{g}/\text{m}^3$  to 42.3  $\mu\text{g}/\text{m}^3$  and PM<sub>10</sub> from 47.2  $\mu\text{g}/\text{m}^3$  to 60.2  $\mu\text{g}/\text{m}^3$ . In the core zone the PM<sub>2.5</sub> and PM<sub>10</sub> values are within the threshold value i.e. 60  $\mu\text{g}/\text{m}^3$  for PM<sub>2.5</sub> and 100  $\mu\text{g}/\text{m}^3$  for PM<sub>10</sub> as per the guideline of NAAQS. Concentration of SO<sub>2</sub> and NO<sub>2</sub> are also found within the limit of 80  $\mu\text{g}/\text{m}^3$  as per the guideline of NAAQS in all the sampling sites of core zone of the mine. The PM<sub>2.5</sub>, PM<sub>10</sub>, SO<sub>2</sub> and NO<sub>2</sub> in the working zone of the mine are in lower in concentration due to rain.

During monsoon season, the PM<sub>2.5</sub> concentration at R. R. Colony (Kajari Village) in buffer zone is in the range of 36.8  $\mu\text{g}/\text{m}^3$  to 37.2  $\mu\text{g}/\text{m}^3$  and the concentration of PM<sub>10</sub> ranges from 42.7  $\mu\text{g}/\text{m}^3$  to 44.1  $\mu\text{g}/\text{m}^3$ . The PM<sub>2.5</sub> concentration at Batsara Village is in the range of 36.2  $\mu\text{g}/\text{m}^3$  to 40.8  $\mu\text{g}/\text{m}^3$  and the concentration of PM<sub>10</sub> ranges from 45.0  $\mu\text{g}/\text{m}^3$  to 55.0  $\mu\text{g}/\text{m}^3$ . In the buffer zone both the values are within the threshold value i.e. 60  $\mu\text{g}/\text{m}^3$  for PM<sub>2.5</sub> & 100  $\mu\text{g}/\text{m}^3$  for PM<sub>10</sub> as per the guideline of NAAQS. Concentration of SO<sub>2</sub> and NO<sub>2</sub> are also found within the limit 80  $\mu\text{g}/\text{m}^3$  as per the guideline of NAAQS in all the sampling sites of buffer zone of the mine.

## 3.2 WATER ENVIRONMENT

### 3.2.1. SOURCES OF WATER POLLUTION

#### Mine Water

No adverse impact on surface water is anticipated as the main surface water regime is not proposed to be disturbed except for the drainage having their catchment within the ML area. The mine water, which is mainly rain water and ground water seepage, is used for industrial

purposes like dust suppression by water tankers in haul roads, approach roads, stockyards and watering of plants in the overburden dumps & office premises.

### **Domestic Effluents/Sewage**

There are minimum housing facilities within the ML area for essential services comprising about 100 inhabitants. The domestic wastes from these houses are led to septic tanks. As the domestic waste water is minimum, the possibility of pollution is remote/insignificant. However, proper care has been taken up in the shelters area of inhabitants for sewage discharge.

### **3.2.2 INSTRUMENTS USED**

- a) pH and Conductivity meter
- b) Ion Meter,
- c) COD Analyser,
- d) BOD Analyser,
- e) Water Analysis Kit, (HACH, DR - 2000)
- f) Microwave Digestion
- g) UV-VIS Spectrophotometer (Simazdo)
- h) Atomic Absorption Spectrophotometer (Varian)
- i) Ion Chromatograph (Dionex/Metrohm)
- j) Flame Photometer
- k) ICP-MS (Perkin Elmer)

### **3.2.3 WATER QUALITY OF THE AREA**

To assess the water quality of the area mine water, ground water and surface water were collected and analysed. During the lean periods, mine water is used for water spraying on haul roads, plantation and other mining activities. To assess the water quality of the area water samples from six locations namely Bagwania mine pit water, effluent water from settling pond, tube well water of R. R. Colony, tube well water of Batsara village and upstream as well as downstream of Koyal river water to the mine site were collected during

summer season. During monsoon season water samples from eight locations namely Muneshwar mine pit water, effluent water from settling pond, Bagwania mine pit water, Mistri mine pit water, tube well water of Kajari village, tube well water of Batsara village and upstream as well as downstream of Koyal river water to the mine site were collected. The analysis was carried out in the field as well as CSIR-CIMFR Laboratory and results are presented from **Table 5 to 10**.

Water quality of nearby well and tube well show that there is no significant impact of mining on water quality of region. TSS, TDS, Oil & Grease, COD, trace metals and other parameters are found within their respective threshold limits. During summer and monsoon seasons the TDS values in R. R. Colony (Kalari Village) and Batsara villages are also lower than their desirable limit of 500mg/l. During summer the alkalinity value at R. R. colony is slightly higher than 200mg/l while at Batsara village the alkalinity is lower than their standard value. During monsoon at both the villages, the alkalinity values are higher than 200mg/l. The water quality of all the mine pit collected also does not show any high value as it remains within the pit, where the contaminants settle before the mine water used for industrial purposes. The mine water quality is well within the prescribed limit of MoEF&CC Schedule-VI standard. As far as Koyal river water is concerned, its quality shows its acceptability as is not affected by Kathautia mine effluents. The level of TSS, TDS and DO in the river water were found within threshold limit during summer and monsoon season in comparison to IS:2296, surface waters Class-C.

**Table 5: Mine Discharge Water Quality Data**

Area: Core Zone	Season: Summer
Project: Kathautia OC Mine	Date of Sampling: 14.06.2018
Name of the Sampling Station:	
W <sub>1</sub> - Bagwania Mine Pit Water	W <sub>2</sub> - Effluent water from Settling Pond No.-2

Sl. No.	Parameters	Station Code		MoEF Sch.-VI Standard
		W <sub>1</sub>	W <sub>2</sub>	
1.	Colour, Hazen units, Max	<5	Sample not available.	5
2.	Odour	#		#
3.	Total suspended solids, mg/l, Max	56		100
4.	pH	7.34		6.5-8.5
5.	Temperature ( <sup>0</sup> C)	30.5		\$
6.	Oil & Grease, mg/l, Max	3.2		10
7.	BOD (3days at 27 <sup>0</sup> C), mg/l, Max	3.6		30
8.	COD, mg/l, Max	45.0		250
9.	Phenolic compounds (as C <sub>6</sub> H <sub>5</sub> OH), mg/l, Max	<0.001		1.0
10.	Arsenic (as AS), mg/l, Max	<0.001		0.2
11.	Lead (as Pb), mg/l, Max	<0.001		0.1
12.	Cadmium (as Cd), mg/l, Max	<0.001		2.0
13.	Hexavalent Chromium (as Cr <sup>6+</sup> ), mg/l, Max	0.001		0.1
14.	Total Chromium (as Cr), mg/l, Max	0.002		2.0
15.	Copper (as Cu), mg/l, Max	<0.001		3.0
16.	Zinc (as Zn), mg/l, Max	<0.001		5.0
17.	Selenium (as Se), mg/l, Max	<0.001		0.05
18.	Nickel (as Ni), mg/l, Max	0.004		3.0
19.	Fluorides (as F), mg/l, Max	1.09		2.0
20.	Dissolved Phosphate (as P), mg/l, Max	<0.1		5.0
21.	Manganese (as Mn), mg/l, Max	<0.001		2.0
22.	Iron (as Fe), mg/l, Max	0.349		3.0
23.	Nitrate (as N), mg/l, Max	0.137		10

# Unobjectionable

\$. Temperature shall not exceed 5°C above the receiving water temp.

**Table 6: Ground Water Quality Data**

Area: Core Zone/Buffer Zone	Season: Summer
Project: Kathautia OC Mine	Date of Sampling: 13.06.2018
Name of the Sampling Station:	
W <sub>3</sub> - Tube Well Water R. R. Colony;	W <sub>4</sub> - Tube Well Water Batsara Village;

Sl. No.	Parameters	Station Code		IS-10500: 2012	
		W <sub>3</sub>	W <sub>4</sub>	Acceptable Limit	Permissible Limit in the Absence of Alternate
1	Colour, Hazen units, Max	<5	<5	5	15
2	Odour	Agreeable	Agreeable	Agreeable	Agreeable
3	Taste	Agreeable	Agreeable	Agreeable	Agreeable
4	Turbidity, NTU, Max	1.28	1.05	1.0	5.0
5	pH	7.72	7.34	6.5-8.5	No relaxation
6	Total Hardness (as CaCO <sub>3</sub> )	294	225	200	600
7	Iron (as Fe), mg/l, Max	0.561	0.736	0.3	No relaxation
8	Chloride (as Cl <sup>-</sup> ), mg/l, Max	25.2	9.2	250	1000
9	Total Dissolved Solid, mg/l, Max	367	412	500	2000
10	Calcium (as Ca), mg/l, Max	82.5	57.2	75	200
11	Magnesium (as Mg), mg/l, Max	21.4	20.0	30	100
12	Manganese (as Mn), mg/l, Max	0.002	0.002	0.10	0.30
13	Sulphates (as SO <sub>4</sub> <sup>-</sup> ), mg/l, Max	23.6	7.9	200	400
14	Nitrate (as NO <sub>3</sub> ), mg/l, Max	34.7	16.4	45	No relaxation
15	Fluorides (as F), mg/l, Max	1.20	1.43	1.0	1.5
16	Arsenic (as AS), mg/l, Max	<0.001	<0.001	0.01	0.05
17	Cadmium (as Cd), mg/l, Max	<0.001	<0.001	0.003	No relaxation
18	Lead (as Pb), mg/l, Max	<0.001	<0.001	0.01	No relaxation
19	Copper (as Cu), mg/l, Max	0.005	<0.001	0.05	1.5
20	Hexavalent Chromium (as Cr <sup>6+</sup> ), mg/l, Max	0.001	<0.001	0.05	No relaxation
21	Selenium (as Se), mg/l, Max	0.002	0.001	0.01	No relaxation
22	Silver (as Ag), mg/l, Max	<0.001	<0.001	-	-
23	Zinc (as Zn), mg/l, Max	0.151	0.033	5	15
24	Total Alkalinity, mg/l, Max	242	190	200	600
25	Mineral Oil, mg/l, Max	<0.001	<0.001	0.001	-



**Table 7: Surface Water Quality Data**

<b>Area: Buffer Zone</b>	<b>Season: Summer</b>
<b>Project: Kathautia OC Mine</b>	<b>Date of Sampling: 15.06.2018</b>
<b>Name of the Sampling Station:</b>	
<b>W<sub>5</sub> - Koyal River water, U/S of Mine;</b>	<b>W<sub>6</sub> - Koyal River water, D/S of Mine;</b>

Sl. No.	Parameters	Station Code		(IS: 2296)# Surface Waters Class "C" Tolerance Limits
		W <sub>7</sub>	W <sub>8</sub>	
1	Colour, Hazen units, Max	<5	<5	300
2	Odour	Unobjectionable	Unobjectionable	Unobjectionable
3	Dissolved Oxygen, mg/l, Min.	8.0	6.4	4
4	pH	8.07	7.88	6.5-8.5
5	BOD (3days at 27°C), mg/l, Max	2.1	2.7	3
6	Phenolic compounds (as C <sub>6</sub> H <sub>5</sub> OH), mg/l, Max	<0.001	<0.001	0.005
7	Total Hardness (as CaCO <sub>3</sub> ), mg/l, Max	156	205	NS
8	Iron (as Fe), mg/l, Max	0.29	0.47	50
9	Chloride (as Cl <sup>-</sup> ), mg/l, Max	8.2	8.3	600
10	Total Dissolved Solid, mg/l, Max	174	252	1500
11	Calcium (as Ca), mg/l, Max	47.1	61.0	NS
12	Magnesium (as Mg), mg/l, Max	9.4	12.9	NS
13	Manganese (as Mn), mg/l, Max	0.001	<0.001	NS
14	Sulphates (as SO <sub>4</sub> <sup>-</sup> ), mg/l, Max	10.91	9.26	400
15	Nitrate (as NO <sub>3</sub> ), mg/l, Max	1.24	5.25	50
16	Fluorides (as F), mg/l, Max	0.58	0.62	1.5
17	Arsenic (as AS), mg/l, Max	<0.001	<0.001	0.2
18	Cadmium (as Cd), mg/l, Max	<0.001	<0.001	0.01
19	Lead (as Pb), mg/l, Max	<0.001	<0.001	0.1
20	Copper (as Cu), mg/l, Max	<0.001	<0.001	1.5
21	Hexavalent Chromium (as Cr <sup>6+</sup> ), mg/l, Max	<0.001	<0.001	0.05
22	Selenium (as Se), mg/l, Max	<0.001	<0.001	0.05
23	Zinc (as Zn), mg/l, Max	0.001	<0.001	15

# : Class "C"- Drinking water source with conventional treatment followed by disinfection.  
NS: Not Specified

**Table 8: Mine Discharge Water Quality Data**

<b>Area: Core Zone</b>	<b>Season: Monsoon</b>
<b>Project: Kathautia OC Mine</b>	<b>Date of Sampling: 30.08.2018</b>
<b>Name of the Sampling Station:</b>	
<b>W<sub>1</sub>- Muneswar Mine Pit Water</b>	<b>W<sub>2</sub>- Effluent water from Settling Pond No.-2</b>
<b>W<sub>3</sub>- Bagwania Mine Pit Water</b>	<b>W<sub>4</sub>- Mistri Mine Pit Water</b>

Sl. No.	Parameters	Station Code				MoEF Sch.-VI Standard
		W <sub>1</sub>	W <sub>2</sub>	W <sub>3</sub>	W <sub>4</sub>	
1.	Colour, Hazen units, Max	<5	<5	<5	<5	5
2.	Odour	#	#	#	#	#
3.	Total suspended solids, mg/l, Max	35	24	36	39	100
4.	pH	8.04	8.09	8.16	8.24	6.5-8.5
5.	Temperature (°C)	21.7	21.9	21.8	21.7	\$
6.	Oil & Grease, mg/l, Max	1.0	0.4	0.8	0.9	10
7.	BOD (3days at 27°C), mg/l, Max	1.8	1.2	1.5	1.9	30
8.	COD, mg/l, Max	28.0	12.4	26.7	22.5	250
9.	Phenolic compounds (as C <sub>6</sub> H <sub>5</sub> OH), mg/l, Max	<0.001	<0.001	<0.001	<0.001	1.0
10.	Arsenic (as AS), mg/l, Max	<0.001	<0.001	<0.001	<0.001	0.2
11.	Lead (as Pb), mg/l, Max	<0.001	<0.001	<0.001	<0.001	0.1
12.	Cadmium (as Cd), mg/l, Max	<0.001	<0.001	<0.001	<0.001	2.0
13.	Hexavalent Chromium (as Cr <sup>6+</sup> ), mg/l, Max	0.004	0.004	0.004	0.004	0.1
14.	Total Chromium (as Cr), mg/l, Max	0.006	0.005	0.005	0.006	2.0
15.	Copper (as Cu), mg/l, Max	<0.001	<0.001	<0.001	<0.001	3.0
16.	Zinc (as Zn), mg/l, Max	0.002	0.001	0.001	0.001	5.0
17.	Selenium (as Se), mg/l, Max	<0.001	<0.001	<0.001	<0.001	0.05
18.	Nickel (as Ni), mg/l, Max	0.005	0.005	0.005	0.005	3.0
19.	Fluorides (as F), mg/l, Max	0.86	0.92	0.70	1.32	2.0
20.	Dissolved Phosphate (as P), mg/l, Max	<0.1	<0.1	<0.1	<0.1	5.0
21.	Manganese (as Mn), mg/l, Max	0.002	0.002	0.002	0.001	2.0
22.	Iron (as Fe), mg/l, Max	0.637	0.630	0.643	0.626	3.0
23.	Nitrate (as N), mg/l, Max	1.99	0.80	0.82	0.77	10

# Unobjectionable  
\$: Temperature shall not exceed 5°C above the receiving water temp.

Table 9: Ground Water Quality Data

Area: Core Zone/Buffer Zone	Season: Monsoon
Project: Kathautia OC Mine	Date of Sampling: 29.08.2018
Name of the Sampling Station:	
W <sub>5</sub> - Tube Well Water Kajari Village;	W <sub>6</sub> - Tube Well Water Batsara Village;

Sl. No.	Parameters	Station Code		IS-10500: 2012	
		W <sub>5</sub>	W <sub>6</sub>	Acceptable Limit	Permissible Limit in the Absence of Alternate
1	Colour, Hazen units, Max	<5	<5	5	15
2	Odour	Agreeable	Agreeable	Agreeable	Agreeable
3	Taste	Agreeable	Agreeable	Agreeable	Agreeable
4	Turbidity, NTU, Max	1.05	0.94	1.0	5.0
5	pH	7.06	7.11	6.5-8.5	No relaxation
6	Total Hardness (as CaCO <sub>3</sub> )	336	366	200	600
7	Iron (as Fe), mg/l, Max	1.460	0.971	0.3	No relaxation
8	Chloride (as Cl <sup>-</sup> ), mg/l, Max	15.0	22.5	250	1000
9	Total Dissolved Solid, mg/l, Max	370	489	500	2000
10	Calcium (as Ca), mg/l, Max	105.3	90.0	75	200
11	Magnesium (as Mg), mg/l, Max	17.9	34.5	30	100
12	Manganese (as Mn), mg/l, Max	0.005	0.083	0.10	0.30
13	Sulphates (as SO <sub>4</sub> <sup>2-</sup> ), mg/l, Max	11.8	20.0	200	400
14	Nitrate (as NO <sub>3</sub> <sup>-</sup> ), mg/l, Max	9.79	0.27	45	No relaxation
15	Fluorides (as F), mg/l, Max	0.55	0.86	1.0	1.5
16	Arsenic (as AS), mg/l, Max	<0.001	<0.001	0.01	0.05
17	Cadmium (as Cd), mg/l, Max	<0.001	<0.001	0.003	No relaxation
18	Lead (as Pb), mg/l, Max	<0.001	<0.001	0.01	No relaxation
19	Copper (as Cu), mg/l, Max	0.002	0.001	0.05	1.5
20	Hexavalent Chromium (as Cr <sup>6+</sup> ), mg/l, Max	0.007	0.009	0.05	No relaxation
21	Selenium (as Se), mg/l, Max	<0.001	<0.001	0.01	No relaxation
22	Silver (as Ag), mg/l, Max	<0.001	<0.001	-	-
23	Zinc (as Zn), mg/l, Max	0.009	1.327	5	15
24	Total Alkalinity, mg/l, Max	248	308	200	600
25	Mineral Oil, mg/l, Max	<0.001	<0.001	0.001	-

Table 10: Surface Water Quality Data

Area: Buffer Zone	Season: Monsoon
Project: Kathautia OC Mine	Date of Sampling: 29.08.2018
Name of the Sampling Station:	
W <sub>7</sub> - Koyal River water, U/S of Mine;	W <sub>8</sub> - Koyal River water, D/S of Mine;

Sl. No.	Parameters	Station Code		(IS: 2296)# Surface Waters Class "C" Tolerance Limits
		W <sub>7</sub>	W <sub>8</sub>	
1	Colour, Hazen units, Max	<5	<5	300
2	Odour	Unobjectionable	Unobjectionable	Unobjectionable
3	Dissolved Oxygen, mg/l, Min.	7.4	4.2	4
4	pH	8.01	7.50	6.5-8.5
5	BOD (3days at 27°C), mg/l, Max	1.5	2.6	3
6	Phenolic compounds (as C <sub>6</sub> H <sub>5</sub> OH), mg/l, Max	<0.001	<0.001	0.005
7	Total Hardness (as CaCO <sub>3</sub> ), mg/l, Max	131	160	NS
8	Iron (as Fe), mg/l, Max	0.479	0.595	50
9	Chloride (as Cl <sup>-</sup> ), mg/l, Max	12.5	25.0	600
10	Total Dissolved Solid, mg/l, Max	143	207	1500
11	Calcium (as Ca), mg/l, Max	40.3	49.6	NS
12	Magnesium (as Mg), mg/l, Max	7.3	8.8	NS
13	Manganese (as Mn), mg/l, Max	0.002	0.001	NS
14	Sulphates (as SO <sub>4</sub> <sup>2-</sup> ), mg/l, Max	14.84	21.34	400
15	Nitrate (as NO <sub>3</sub> <sup>-</sup> ), mg/l, Max	3.83	7.59	50
16	Fluorides (as F), mg/l, Max	0.60	0.57	1.5
17	Arsenic (as AS), mg/l, Max	<0.001	<0.001	0.2
18	Cadmium (as Cd), mg/l, Max	<0.001	<0.001	0.01
19	Lead (as Pb), mg/l, Max	<0.001	<0.001	0.1
20	Copper (as Cu), mg/l, Max	0.001	0.001	1.5
21	Hexavalent Chromium (as Cr <sup>6+</sup> ), mg/l, Max	0.004	0.004	0.05
22	Selenium (as Se), mg/l, Max	<0.001	<0.001	0.05
23	Zinc (as Zn), mg/l, Max	0.013	0.012	15

# : Class "C"- Drinking water source with conventional treatment followed by disinfection.  
NS: Not Specified

### 3.3 NOISE ENVIRONMENT

Noise is undesirable and unpleasant sound produced by the vibration of bodies or molecules of the medium and propagates as a pressure perturbation. It disturbs man's work, sleep and communication. It damages hearing and evokes other physiological reactions. Mining is the third largest industry in terms of employment and the recent trends of mechanization has changed the working environment to noisy environment leading to higher sound levels.

#### 3.3.1 SOURCES OF NOISE

Noise produced at different levels by different equipments in the open cast mine are summarized in the **Table 11**.

**Table 11: Noise Generating Mining Equipments**

S. N.	Equipment / Operation	Noise level dB(A)
1	Feeder breaker	82-100
2	Dumpers	100-115
3	Shovels	80-107
4	Dozers	84-107
5	Front End loader	83-101
6	Electric motors, gear drivers, hoppers, drilling & main pump	85-95
7	Belt conveyer	90-92
8	Drill	110-115

Noise level study at Kathautia Open Cast Coal Mine was carried out in buffer as well as core zone. Five noise level monitoring locations in core zone and two noise level monitoring locations in buffer zone were fixed-up and get representative values during summer and monsoon seasons.

#### 3.3.2 INSTRUMENTS USED

Sound level study is carried by using Mip-oy Integrated Sound Level Meter Meeting IEC-179A measuring average peak and Low values in Day and Night time.

### 3.3.3 RESULTS & DISCUSSION

Results are shown from **Table 12** to **21** for ambient noise levels of core and buffer zones during summer and monsoon seasons. The average peak values at the nearby villages are found well below the standard values of 55 & 45 dB (A) for day & Night. In core zone maximum noise levels and average noise levels are also well within the prescribed limit of 75 & 70 dB (A) for Day & Night respectively.

**Table 9: Noise Level in Core Zone of the Study Area (April, 2018)**

Date of Sampling:		Noise level dB(A) average					
23.04.2018 to 25.04.2018		Day Time			Night Time		
Stn. Code	Location	Min.	Max.	Average	Min.	Max.	Average
N <sub>1</sub>	Near Mine Office	38.0	72.2	56.6	35.5	60.1	46.8
N <sub>2</sub>	Coal Face	37.2	68.3	55.8	35.8	58.3	46.2
N <sub>3</sub>	Near OB dump	36.4	65.1	57.1	35.2	55.0	44.5
N <sub>4</sub>	Stockyard	36.8	63.8	56.8	37.0	54.4	46.0
N <sub>5</sub>	Haul Road	37.4	74.5	60.2	37.2	62.2	50.2
<b>Standards as per CPCB</b>		<b>75</b>			<b>70</b>		

**Table 10: Noise Level in Buffer Zone of the Study Area (April, 2018)**

Date of Sampling:		Noise level dB(A) average					
23.04.2018 to 25.04.2018		Day Time			Night Time		
Stn. Code	Location	Min.	Max.	Average	Min.	Max.	Average
N <sub>6</sub>	R. R. Colony	36.5	64.6	52.4	34.6	50.8	43.2
N <sub>7</sub>	Batsara Village	36.1	62.5	51.2	35.0	52.6	42.4
<b>Standards as per CPCB</b>		<b>55</b>			<b>45</b>		

**Table 11: Noise Level in Core Zone of the Study Area (June, 2018)**

Date of Sampling:		Noise level dB(A) average					
12.06.2018 to 15.06.2018		Day Time			Night Time		
Stn. Code	Location	Min.	Max.	Average	Min.	Max.	Average
N <sub>1</sub>	Near Mine Office	37.2	67.7	51.0	36.8	57.2	45.4
N <sub>2</sub>	Coal Face	36.6	67.2	52.6	35.2	55.2	44.0
N <sub>3</sub>	Near OB dump	36.8	64.7	51.2	34.7	54.2	42.9
N <sub>4</sub>	Stockyard	37.0	61.2	54.8	36.5	55.0	44.2
N <sub>5</sub>	Haul Road	37.5	73.8	58.2	36.8	58.6	48.2
<b>Standards as per CPCB</b>		<b>75</b>			<b>70</b>		

**Table 12: Noise Level in Buffer Zone of the Study Area (June, 2018)**

Date of Sampling:		Noise level dB(A) average					
12.06.2018 to 15.06.2018		Day Time			Night Time		
Stn. Code	Location	Min.	Max.	Average	Min.	Max.	Average
N <sub>6</sub>	R. R. Colony	36.1	63.5	51.4	34.8	52.6	44.7
N <sub>7</sub>	Batsara Village	35.5	61.0	50.5	34.2	51.0	42.8
<b>Standards as per CPCB</b>		<b>55</b>			<b>45</b>		

**Table 13: Noise Level in Core Zone of the Study Area (July, 2018)**

Date of Sampling:		Noise level dB(A) average					
27.07.2018 to 29.07.2018		Day Time			Night Time		
Stn. Code	Location	Min.	Max.	Average	Min.	Max.	Average
N <sub>1</sub>	Near Mine Office	37.0	66.4	51.4	36.2	57.8	45.2
N <sub>2</sub>	Coal Face	36.0	68.6	52.0	35.0	54.0	43.1
N <sub>3</sub>	Near OB dump	36.2	62.8	50.5	34.9	53.5	42.3
N <sub>4</sub>	Stockyard	36.0	62.5	53.1	36.0	54.7	43.2
N <sub>5</sub>	Haul Road	37.8	71.6	56.1	36.5	58.0	45.6
<b>Standards as per CPCB</b>		<b>75</b>			<b>70</b>		

**Table 14: Noise Level in Buffer Zone of the Study Area (July, 2018)**

Date of Sampling:		Noise level dB(A) average					
27.07.2018 to 29.07.2018		Day Time			Night Time		
Stn. Code	Location	Min.	Max.	Average	Min.	Max.	Average
N <sub>6</sub>	R. R. Colony	36.4	61.6	50.3	35.2	55.2	44.0
N <sub>7</sub>	Batsara Village	35.7	60.7	50.8	34.6	51.7	42.1
<b>Standards as per CPCB</b>		<b>55</b>			<b>45</b>		

**Table 15: Noise Level in Core Zone of the Study Area (August, 2018)**

Date of Sampling:		Noise level dB(A) average					
27.08.2018 to 29.08.2018		Day Time			Night Time		
Stn. Code	Location	Min.	Max.	Average	Min.	Max.	Average
N <sub>1</sub>	Near Mine Office	37.5	67.0	53.6	36.2	57.0	45.4
N <sub>2</sub>	Coal Face	36.4	66.6	52.4	35.5	55.6	43.6
N <sub>3</sub>	Near OB dump	36.0	63.5	50.8	34.5	54.0	42.6
N <sub>4</sub>	Stockyard	36.8	65.7	52.6	35.8	56.0	44.5
N <sub>5</sub>	Haul Road	37.3	72.6	57.1	36.0	58.2	47.1
<b>Standards as per CPCB</b>		<b>75</b>			<b>70</b>		

**Table 16: Noise Level in Buffer Zone of the Study Area (August, 2018)**

Date of Sampling:		Noise level dB(A) average					
27.08.2018 to 29.08.2018		Day Time			Night Time		
Stn. Code	Location	Min.	Max.	Average	Min.	Max.	Average
N <sub>6</sub>	R. R. Colony	36.6	63.0	51.6	35.5	54.2	43.5
N <sub>7</sub>	Batsara Village	35.2	61.8	50.8	34.6	52.5	42.1
<b>Standards as per CPCB</b>		<b>55</b>			<b>45</b>		

**Table 17: Noise Level in Core Zone of the Study Area (September, 2018)**

Date of Sampling:		Noise level dB(A) average					
28.09.2018 to 30.09.2018		Day Time			Night Time		
Stn. Code	Location	Min.	Max.	Average	Min.	Max.	Average
N <sub>1</sub>	Near Mine Office	37.0	70.2	55.7	36.5	58.1	47.3
N <sub>2</sub>	Coal Face	36.0	68.3	52.0	35.0	55.4	44.2
N <sub>3</sub>	Near OB dump	36.2	64.4	51.1	35.1	55.5	44.8
N <sub>4</sub>	Stockyard	36.5	65.2	53.3	36.0	56.7	45.1
N <sub>5</sub>	Haul Road	37.8	74.5	58.8	36.5	58.7	50.0
<b>Standards as per CPCB</b>		<b>75</b>			<b>70</b>		

**Table 18: Noise Level in Buffer Zone of the Study Area (September, 2018)**

Date of Sampling:		Noise level dB(A) average					
28.09.2018 to 30.09.2018		Day Time			Night Time		
Stn. Code	Location	Min.	Max.	Average	Min.	Max.	Average
N <sub>6</sub>	R. R. Colony	36.2	64.2	52.4	35.5	56.3	43.3
N <sub>7</sub>	Batsara Village	35.0	60.5	50.2	34.4	51.0	42.8
<b>Standards as per CPCB</b>		<b>55</b>			<b>45</b>		

#### 4.0 CONCLUSION

On the basis of the data generated it has been found that the environmental scenario in and around mining area of Kathautia Open Cast Mine with respect to air, water and noise are well within the permissible limits.

#### 5.0 RECOMMENDATIONS & FOLLOW-UP ACTION

The study indicates that air quality around the Kathautia Open Cast Coal Mine is found to be within the threshold limit as per the guideline of NAAQS, 2009. However, the mine is not in working during the monitoring period. Water quality of the surrounding water resources are also not found polluted by mine effluent. For the best practice of coal mining in future, Environmental Management System should always be considered with following measures:

- ✓ Frequency of spraying of water on the haul roads for controlling the dust to its minimum level may be increased.
- ✓ Regular maintenance of the heavy earth moving machines.
- ✓ Mine water collection in settling tank before its discharge.
- ✓ Garland drainage should be made around the dumps.
- ✓ Reclamation and revegetation of overburden dumps should be done to control soil erosion, denudation of agricultural land and nearby riverine system, wetlands and to improves the aesthetics of the area.
- ✓ Dumps brought under biological reclamation should not be made active.
- ✓ The mine management has been implementing, these measures to make mining operation eco-friendly in this coal mine of M/s Hindalco Industries Ltd, Daltonganj, Jharkhand.