DECLARATION OF PERFORMANCE

ACCORDING TO ANNEX IIICONSTRUCTION PRODUCTS REGULATIONS (305/2011/EU) & REGULATION (EU) NO. 574/2014

DOP NO: - AA3004-H24-(0.2 to 0.5)

01. Unique identification code of the product type: AA3004-H24-(0.2 to 0.5)

02. Intended Use/es: Internal & External Load Bearing Structural & Constructional work.

03. Manufacturer: Hindalco Industries Ltd

Hirakud- FRP, HIRAKUD,

Sambalpur – Odisha

Pin- 768016

04. Authorised Representative : None

05. System/s of AVCP: System 2+

6a. Harmonised Standard: EN 15088:2005, Annex ZA.

Notified body/ies:

TUV NORD systems GmbH and co. KG, D-22525 Hamburg, Kenn. Nr.0045 TUV NORD systems GmbH and co. KG, Notified body, Reg No. 0045 performed initial inspection of manufacturing plant under system 2+ and issued system of conformity of the factory production control.

6b. European Assessment document : Not ApplicableEuropean Technical Assessment: Not ApplicableTechnical Assessment Body:Not ApplicableNotified Body/ies:Not Applicable

Mandated/Essential Characteristics	Performance	Notes, expression of performance
		-
Tolerances on dimension and shape	Flat Rolled Product	Pass
Elongation	Minimum 3% Elongation on 50mm GL	Pass
Ultimate tensile strength	220-265 MPa in Transverse direction	Pass
Yeild Strength (0.2% OFFSET), MPa	170 MPa Minimum in TransversePassdirection	
Bendability	NO Performance Determined	_
Weldability	NO Performance Determined as not applicable to our product	-
Fatigue Strength	NO Performance Determined asnot applicable to our product	
Dangerous (regulated) Substances	NO Performance Determined asnot applicable to our product	
Durability (against Corrosion)	NO Performance Determined as not applicable to our product_	

10. The performance of the product performance identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) no 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Place Issued: - Hindalco Industries Ltd. Hirakud- FRP, Hiraklud, Sambalpur – Odisha Pin- 768016 Date & Signature

HINDALCO HIN				
21				
0045-CPR-XXXX				
DOP NO- AA3004-H24-(0.2 to 0.5)				
DOI NO ² MASOOT 1124 (0.2 to 0.5)				
EN-15088-2005 Intended Use-Internal & External Load Bearing Structural & Constructional work. Flat Rolled Profile				
Tolerance & Dimension, & Shape				
Elongation after Fracture		EN485-1		
Minimum Tensile strength		EN485-2		
Lower Yield strength of stress at 0.2 % & non		EN485-3	Pass/Fail	
proportional elongation		EN485-4	,	
Bend diameter				
Lot TKT.				
PART NO		DATE		
DIMENSION		TEMPER		
NET WT.		GROSS WT.		

