DECLARATION OF PERFORMANCE

ACCORDING TO ANNEX IIICONSTRUCTION PRODUCTS REGULATIONS (305/2011/EU) & REGULATION (EU) NO. 574/2014

DOP NO: - AA5052-H32-(3.0 to 4.80)

01. Unique identification code of the product type: AA5052-H32-(3.0 to 4.80)
02. Intended Use/es: Internal & External Load Bearing Structural & Constructional work.

03. Manufacturer: Hindalco Industries Ltd Hirakud- FRP, HIRAKUD, Sambalpur – Odisha

Pin- 768016

04. Authorised Representative : None

05. System/s of AVCP: System 2+

6a. Harmonised Standard: EN 15088:2005, Annex ZA.

Notified body/ies:

TUV NORD systems GmbH and co. KG, D-22525 Hamburg, Kenn. Nr.0045 TUV NORD systems GmbH and co. KG, Notified body, Reg No. 0045 performed initial inspection of manufacturing plant under system 2+ and issued system of conformity of the factory production control.

6b. European Assessment document : Not ApplicableEuropean Technical Assessment:Not ApplicableTechnical Assessment Body:Not ApplicableNotified Body/ies:Not Applicable

09. DECLARED PERFORMANCE/s:

Mandated/Essential Characteristics	Performance	Notes, expression of performance	
Tolerances on dimension and shape	Flat Rolled Product	Pass	
Elongation	Minimum10 % Elongation onPass50mm GL		
Ultimate tensile strength	210-260 MPa in Transverse direction	Pass	
Yeild Strength (0.2% OFFSET), MPa	130 MPa Minimum in Transverse direction	Pass	
Bendability	NO Performance Determined	_	
Weldability	NO Performance Determined as not applicable to our product	_	
Fatigue Strength	NO Performance Determined as not applicable to our product	_	
Dangerous (regulated) Substances	NO Performance Determined as		
Durability (against Corrosion)	NO Performance Determined as not applicable to our product_		

10. The performance of the product performance identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) no 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Place Issued: - Hindalco Industries Ltd. Hirakud- FRP, Hiraklud, Sambalpur – Odisha Pin- 768016 Date & Signature

HINDALCO HIN				
Web: www.hindalco.com 0045				
21 0045-CPR-XXXX DOP NO- AA5052 H32 (3.0 to 4.80)				
EN-15088-2005 Intended Use-Internal & External Load Bearing Structural & Constructional work. Flat Rolled Profile				
Tolerance & Dimension, & Shape Elongation after Fracture Minimum Tensile strength Lower Yield strength of stress at 0.2 % & non proportional elongation Bend diameter		EN485-1 EN485-2 EN485-3 EN485-4	Pass/Fail	
Lot TKT.				
PART NO		DATE		
DIMENSION		TEMPER		
NET WT.		GROSS WT.		

