## **DECLARATION OF PERFORMANCE**

## ACCORDING TO ANNEX IIICONSTRUCTION PRODUCTS REGULATIONS (305/2011/EU) & REGULATION (EU) NO. 574/2014

## DOP NO: AA5086H24 or H34(0.50 to 1.50)

**01**. Unique identification code of the product type AA5086H24 or H34(0.50 to 1.50)

02. Intended Use/es: Internal & External Load Bearing Structural & Constructional work.

03. Manufacturer: Hindalco Industries Ltd

Hirakud- FRP, HIRAKUD,

Sambalpur – Odisha

Pin- 768016

04. Authorised Representative : None

05. System/s of AVCP: System 2+

6a. Harmonised Standard: EN 15088:2005, Annex ZA.

Notified body/ies:

TUV NORD systems GmbH and co. KG, D-22525 Hamburg, Kenn. Nr.0045 TUV NORD systems GmbH and co. KG, Notified body, Reg No. 0045 performed initial inspection of manufacturing plant under system 2+ and issued system of conformity of the factory production control.

6b. European Assessment document : Not Applicable
European Technical Assessment: Not Applicable
Technical Assessment Body: Not Applicable
Notified Body/ies: Not Applicable

09. DECLARED PERFORMANCE/s:

Mandated/Essential Characteristics	Performance	Notes, expression of performance	
Tolerances on dimension and shape	Flat Rolled Product	Pass	
Elongation	Minimum 5 % Elongation on 50mm GL	Pass	
Ultimate tensile strength	300-360 MPa in Transverse direction	Pass	
Yeild Strength (0.2% OFFSET), MPa	220 MPa Minimum in Transverse direction	Pass	
Bendability	NO Performance Determined	-	
Weldability	NO Performance Determined as not applicable to our product	-	
Fatigue Strength	NO Performance Determined as not applicable to our product	-	
Dangerous (regulated ) Substances	NO Performance Determined as not applicable to our product	-	
Durability (against Corrosion)	NO Performance Determined as		

10. The performance of the product performance identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) no 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Place Issued: - Hindalco Industries Ltd. Hirakud- FRP, Hiraklud, Sambalpur – Odisha Pin- 768016 Date & Signature

HINDALCO HIN					
21					
0045-CPR-XXXX					
DOP NO : AA5086H24 or H34(0.50 to 1.50)					
	EN-15088-2005				
Intended Use-	Intended Use-Internal & External Load Bearing Structural & Constructional work.				
	Flat R	olled Profile			
Tolerance & Dimension, & Shape					
Elongation after Fracture		EN485-1			
Minimum Tensile strength		EN485-2			
Lower Yield strength of stress at 0.2 % & non		EN485-3	Pass/Fail		
proportional elongation		EN485-4			
Bend diameter					
Lot TKT.					
PART NO		DATE			
DIMENSION		TEMPER			
NET WT.		GROSS WT.			

