The status of Environmental Clearance accorded by Ministry of Environment and Forests, I.A. Division, New Delhi to M/s HINDALCO INDUSTRIES LIMITED, CHOTAMURI, Jharkhand for expansion of Alumina Refinery from 125000 MT/Year (nominal) Alumina Production capacity to 575000 MT per year(nominal) **For a Period Oct'14 – March'15**.

Your letter ref. no. J-11011/131/2005-IA.II (I) dated 20.09.05

## A. SPECIFIC CONDITIONS

Sl.No	Condition	Compliance as on March'15
i)	The gaseous emissions from various	a) Pollution control equipments are designed
	units shall conform to the standards	to ensure the gaseous emissions confirm to
	prescribed from time to time. The State	the standards prescribed by statutory
	Board may specify more stringent	authority.
	standards for the relevant parameters	
	keeping in view the nature of the	b) Ambient Air Quality data is regularly
	industry, its size and location. At no	monitored and records are maintained and
	time the emission level should go	sent to State Pollution Control Board
	beyond the prescribed standards. In the	regularly. Please refer Annexure – I- AAQ
	event of failure of any pollution control	monitoring records.
	system adopted by the unit, the respective unit should not be restarted	
	until the control measures are rectified	
	to achieve the desired efficiency.	
	Ambient Air Quality data should be	
	regularly monitored and records	
	maintained and report submitted to the	
	Ministry /CPCB/Jharkhand State	
	Pollution Control board once in six	
	months.	
ii)	There shall be no discharge of process	a) Process ETP has been commissioned and
	effluent. As reflected in the EIA/EMP	operating satisfactorily.
	report, the process waste water	Based on present plant capacity, process
	generation shall increase from 528m3/d	effluent is being fully recycled in the plant
	to 5092m3/d. About 802m3/d of waste	process. Annexure - III- water quality report.
	water will be recycled. Remaining	b) We have initiated a series of actions to
	4290m3/d will be recycled back to the	reduce fresh water consumption. These
	process after treatment in the ETP. In addition, efforts shall be made to re-use	actions are primarily focusing on reducing fresh water consumption, in-process
	wastewater from the existing plant. The	fresh water consumption, in-process recycling of effluents and use excess
	domestic wastewater shall be treated in	condensate to replace fresh water intake.
	STP to meet prescribed standards. The	c) Domestic STP has been commissioned and
	company shall undertake water	operating satisfactorily. The treated water is
	conservation measures by recycling of	being reused for gardening and dust

	power plant blow downs and domestic effluent in the refinery process. The storm water management shall be by use of water for sprinkling, recycling to process, ash moistening and plant keep up.	suppression. d) Recently we have installed Online Effluent (SSTP & ETP) Water Quality Monitoring System. Presently it is connected to Aaxis Nano Technology Pvt. Ltd sever. All related data e.g. PH, TSS, BOD & COD are being captured and monitored.
iii)	In plant control measures for checking fugitive emission from spillage/raw materials handling shall be provided. Water sprinklers shall be provided to control the fugitive emissions from the active red mud disposal areas and ash coverage in inactive areas.	<ul> <li>a) Water sprinkling system in bauxite and coal storage and handling area is installed and is being operated to mitigate fugitive dust emission.</li> <li>b) Dust suppression system in red mud disposal areas has been strengthened. Sprinkling system is being extended to additional areas as and when exposed. Sprinkling is carried out during summer and windy season.</li> </ul>
		c) Water sprinkling is done through mobile tankers along the roads, inside & outside the periphery of the plant.
iv)	The particulate emissions from the calciners shall be controlled by installation of electrostatic precipitator. The particulate emissions shall not exceed 50mg/Nm3. The company shall install bag filters to control the emissions from the alumina kiln. All the boiler stacks shall be provided with stack height as per the CPCB guidelines. The boiler and calciner stacks shall be equipped with continuous monitoring device to check SPM emission levels.	Pollution control devices have been commissioned along with the ESP and are connected to chimney stack in calciner & boilers complying with the CPCB guidelines. Continuous Emission Monitoring System to check Particulate Matter emission levels has been provided to the CFCB and Boiler stack and is working satisfactorily.
v)	The company shall adopt dry disposal system for red mud disposal and shall provide Geo membrane lining in red mud storage area. The ground water quality shall be monitored at various depths around the red mud ponds and action plan in this regard shall be submitted to the Ministry. The company shall rehabilitate the abandoned red mud pond areas with development of green	a) The dry disposal of mud is being practiced already (Since June'02) in existing red mud pond. b) Recently we have installed Pressure filter to get more solid (> 72%) and enhance pond life. c) We have planned to execute a new technology called controlled modular column (CMC) in RMP area which will increase its life and will eliminate the requirement of new Red Mud pond

		C ( 10
	cover.	for next 10 years. This technology is recommended by CBRI, Roorkee after a series of
		studies and soil analysis of the existing area in
		last one year considering all environment aspects
		last one year considering an environment aspects
		b) NGRI, Hyderabad has conducted a
		comprehensive study of 57 ground water
		sources in the 1 km radius of the RMP during
		pre and post monsoon season of 2006-07. The
		report suggests that there is no impact due to
		the red mud storage. The ground water
		quality is being monitored once in six month
		since June'06, during pre-monsoon and post
		monsoon period. Total 57 ground water
		points, identified by NGRI Hyderabad and
		JSPCB, are monitored within a radius of 1
		km of the pond for salient parameters. The
		report suggests that there is no impact due to
		the red mud storage. The study was further
		continued during 2008-09, 2009-10 & 2011-
		12 and it is extended for the year 2013-14.
		The hydro geological, geophysical, remote
		sensing, water level and water quality-
		monitoring data base, prima facie, does not
		indicate, contamination of groundwater from
		the red mud stacking or red mud ponds. The
		report suggests that there has been no
		significant change as regards fluorides,
		chlorides and TDS concentrations during the
		last 5 year period.
		c) Green belt cover of Red Mud Pond:
		Abandoned red mud pond pond#2 has been
		rehabilitated through green cover in phases
		starting from the year 2005. Expertise
		(external agency) for development of green
		cover by TERI a leading organization in this
		field has been taken. 6000 trees sapling of
		different species have been planted over Nine
		acres of abandoned Red Mud Pond #2. The
		survival rate is 98%.
		d) Around 15000 saplings of different species
		planted over abandoned RMP#2. The survival
• >		rate is 95%.
vi)	As and when the new pond for red mud	New red mud pond will be provided with
	disposal is to be constructed, it shall be	Geo-textile lining, as and when constructed.
	lined with geo lining to prevent leaching	
	of effluent into the ground water.	

vii)	Green belt of adequate width and density shall be developed in 5 ha. of area in addition to 48.97 ha of plant area already under green belt as per the CPCB guidelines.	Complied. a) A total of 15 acres has been covered with green belt by planting about 15000 tree saplings since June 2005 around the company premises. (b) Also refer specific condition(v) Approx 3000 sapling is having been planted during 2011-12 plant and township area. c) We have planted approx 5200 saplings of plant 2012 to 2013 of Ashok, Saagwaan, Gamhar, Chatni, Neem, Babool, Sisham, Pipal, and survival rate is 95% as measured Banyan in and around the factory premises. We have planted approx 2397 no's trees 2013-14. d) This year we have planted approx 3000 of saplings comprising of Ashok, Gamhar, Sisham, Jamu & Neem in and around the factory premises, year April'14 to March'15.
viii)	Occupational Health Surveillance of the workers shall be done on a regular basis and records maintained as per the Factories Act.	OHS for employees are carried out regularly on routine basis at regular interval by our Medical Health Centre and records are maintained and no adverse impacts/deterioration has been evidenced.
ix)	All the recommendations of the Charter for Corporate Responsibility for Environment Protection (CREP) for the aluminium sector shall be strictly implemented.	<ol> <li>Dry disposal of red mud is being practiced since 2002 and the same shall be continued.</li> <li>Recently we have installed Pressure filter to get more solid (&gt; 72%) and enhance pond life.</li> </ol>
		3) We have planned to execute a new technology called controlled modular column (CMC) in RMP area which will increase its life and will eliminate the requirement of new Red Mud pond for next 10 years. This technology is recommended by CBRI, Roorkee after a series of studies and soil analysis of the existing area in last one year considering all environment aspects
		4) New Red Mud Pond will be provided with Geo-textile lining as and when constructed.
		5) Alumina calciners are provided with ESP to maintain emission of 50 mg/Nm3.
		6) New power plant is provided with an ESP to achieve emission less than 100mg/Nm3. A continuous online monitoring system has

	been installed for monitoring the emissions.
	been instance for monitoring the emissions.
	7) Dry fly ash handling system is adopted for captive coal power plant.
	8) 100% Fly ash is being utilized for Flyash brick making and backfilling of coal mine pit at CCL Rajrappa, 45 km from Muri.
	9) We are in touch of some cement and brick making industry for the utilization of Red mud.
	10) Red mud supply to ACC cement Plant has been started since Apr'12 and supply to Krishna Udyog started since Sept'14.
The environmental clearance for the expansion of alumina refinery and establishment of coal based cogeneration proposal is subject to the condition that the company shall not undertake any construction or operation of the proposed expansion activity till the environmental clearance for the linked mining proposal is obtained.	Environmental clearance has been obtained for the new mines leases linked to this project namely Kujam 1, Kujam II & Amtipani.
The project authorities must strictly adhere to the stipulations made by the Jharkhand State Pollution Control Board and the State Government.	The stipulations made by Jharkhand State Pollution Control board/State govt. are being adhered to.
No further expansion or modifications in the plant should be carried out without prior approval of the Ministry of Environment and Forests.	Complied
Adequate ambient air quality-monitoring stations should be established in the downward direction as well as where maximum ground level concentration of SPM, SO2 and NOx are anticipated in consultation with the State Pollution Control Board. Data on ambient air quality, fugitive emission and stack emissions shall be regularly submitted to this Ministry including its Regional	Complied. Please refer Annexure-I- AAQ monitoring report and Annexure –II for stack monitoring report.
	expansion of alumina refinery and establishment of coal based cogeneration proposal is subject to the condition that the company shall not undertake any construction or operation of the proposed expansion activity till the environmental clearance for the linked mining proposal is obtained.  GENERAL CONDITIONS:  The project authorities must strictly adhere to the stipulations made by the Jharkhand State Pollution Control Board and the State Government.  No further expansion or modifications in the plant should be carried out without prior approval of the Ministry of Environment and Forests.  Adequate ambient air quality-monitoring stations should be established in the downward direction as well as where maximum ground level concentration of SPM, SO2 and NOx are anticipated in consultation with the State Pollution Control Board. Data on ambient air quality, fugitive emission and stack emissions shall be regularly submitted to

	Pollution Control Board/Central Pollution Control Board once in six months.	
iv)	Industrial waste water shall be properly collected, treated so as to conform to the standards prescribed under GSR 422 (E) dated 19 <sup>th</sup> May, 1993 and 31 <sup>st</sup> December, 1993 or as amended from time to time. The treated wastewater should be utilized for plantation purpose.	Refer specific condition (ii) (a)
v)	The overall noise levels in and around the plant area shall be kept well within the standard (85 dBA) by providing noise control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise levels should conform to the standards prescribed under EPA Rules, 1989 viz. 75 dBA (daytime) and 70 dBA (night time).	Noise levels in existing plant are largely within stipulated standard. However, uses of Personal Protective equipments like ear plug/ear muffs to reduce the noise level are in practice in few areas like ball mill. Acoustic enclosures are provided in various areas to reduce sources of noise generation.  Annexure - IV.
vi)	The project proponent shall also comply with the environmental protection measures and safeguards recommended in the EIA/EMP report. Further, the company must undertake socioeconomic development activities in the surrounding villages like community development programmes, educational programmes, drinking water supply and health care etc.	a) The EMP's are being implemented as committed in the EIA report. b) Company is regularly undertaking various community development programmes. The annual expenditures incurred during the period on Community Development Programs are 2004-05 (17 lakhs), 2005-06 (21 Lakhs), 2006-07 (32 Lakhs), 2007-08 (67 lakhs), 2008-09 (47 Lakhs), 2009-10 (67.7 Lakhs), 2010-11 (81.07Lakhs), 2011-12 (80 Lakhs), 2013-14 (1.0crore). 2014-15 ((1.0 crore). socio-economic field has been enclosed as <b>Annexure –V.</b>
vii)	The project authorities will provide requisite funds both recurring and non-recurring to implement the conditions stipulated by the Ministry of Environment and Forests as well as the State Government along with the implementation schedule for all the conditions stipulated herein. The funds so provided should not be diverted for any other purposes.	Complied.
viii)	The Regional Office of this Ministry at	Complied.

	Bhubaneswar/Central Pollution Control Board/State Pollution Control Board will monitor the stipulated conditions. A six monthly compliance report and the monitored data along with statistical interpretation should be submitted to them regularly.	
ix)	The project proponent should inform the public that the project has been accorded environmental clearance by the ministry and copies of the clearance letter are available with the State Pollution Control board/Committee and may also be seen at website of the Ministry of Environment and Forests at http:envfor.nic.in. This should be advertised within seven days from the date of issue of the clearance letter, at least in two local newspapers that are widely circulated in the region of which one shall be in the vernacular language of the locality concerned and a copy of the same should be forwarded to the Regional office.	Informed Public through two local Hindi News Papers namely "Prabhat Khabar" & "Hindustan" dated 30 Sept'05 that the project has been accorded environmental clearance by Ministry. Copies of the same have been forwarded to Regional Office at Bhubaneswar on 31st July'2006.
x)	The Project Authorities should inform the Regional Office as well as the Ministry, the date of financial closure and final approval of the project by the concerned authorities and the date of commencing the land development work.	<ul><li>a) Date of financial closure &amp; approval of project: 26 July'04.</li><li>b) Date of commencing land development work: 10 Oct'05.</li></ul>